

Installation:

The L10 Vandal Proof LED Exit can be installed either Ceiling or Wall Mounted. When wall mounted, it can be flat/back to the wall or as a Flag extending from the wall.

All versions (Assembly preparation)

- Remove the 4 security screws which hold the assembly together.
- Remove the bottom cover frame whilst holding the side covers.
- Disengage the Cleverfit Pro from the slide connect bracket.
- Remove the terminal block cover.
- Remove the slide bracket from the top mounting frame.

Ceiling Mount

- Using the Top frame as a guide, mark 4 holes for mounting and one for mains access.
- Install the top frame to the ceiling using appropriate fixings (not supplied).
- Route the power cable through the access hole.
- Install the Cleverfit Pro slide bracket with the power cable through the access hole.
- Connect the power to the terminal block.
- Reinstall the terminal block cover.
- Reinstall the Cleverfit Pro Exit to the slide bracket.

Wall Mount


- Using the solid Polycarbonate sheet as a guide, mark 4 holes for mounting and one for mains access.
- Install the solid Polycarbonate sheet to the wall using appropriate fixings (not supplied).
- Route the power cable through the access hole in the Polycarbonate.
- Position the top frame over the Polycarbonate sheet.
- Install the Cleverfit Pro slide bracket with the power cable through the cable entry.
- Connect the power to the terminal block.
- Reinstall the terminal block cover.
- Reinstall the Cleverfit Pro Exit to the slide bracket.

All versions (Final Assembly)

- Ensure the 2 clear slide covers are inserted back into the bottom frame
- Re-install the bottom frame to the top frame, whilst aligning the side covers into the top frame, using the 4 security screws which hold the assembly together.

Testing and Maintenance

Refer to the Cleverfit Pro Installation Instruction sheet provided with the fitting for all test and maintenance procedures.


Note that in order to scan the LED on the fitting for Clevertest Plus  the bottom part of the vandal proof housing needs to be removed.



L10™ LED Vandal Proof Exit

Installation & Maintenance Instruction Leaflet



NOTE: Standard product codes with this symbol  are enabled with Clevertest Plus capability. Please refer to the operation guide supplied with the product for details.

Australia (Head Office)

Website: www.clevertronics.com.au

Email: info@clevertronics.com.au

Phone: +61 3 9559 2700

Fax: +61 3 9559 2799

UK OFFICE

Website: www.clevertronics.co.uk

362 Stockley Close
West Drayton UB7 9BL
Phone: 01895 430 255



Models: LVELED-xx-yy-vv

Testing:

Manual Test xx = Blank

Zoneworks xx = ZW

Z/W DATA xx = DATA

Zoneworks HIVE xx = HVG

DALI Registered. xx = DALI



Options:

Wall Mount yy = WM

Ceiling Mount yy = CM

Flag Mount yy = FM

Special Sign vv=SP

Important:

It is illegal for anyone, except for a licensed electrician to install or maintain this product. Before installation, ensure that the electricity supply has been switched off and isolated. Installation must be carried out in accordance with the relevant British Standards.

Dimensions:

