



ARGO-1200-DD

Argo 1200mm Weatherproof Batten, Switchable Colour, DALI Driver



PRODUCT INFORMATION	
Part Number	ARGO-1200-DD
MIC	AUB04621000001
Description	Argo 1200mm Weatherproof Batten, Switchable Colour, DALI Driver
Construction	Polycarbonate Base and Diffuser with Captive Stainless-Steel Clips (SS301)
Mounting	Surface mount
Dimensions L x W x H	1265mm x 121mm x 88mm
Weight	2.4 kg
Diffuser	Polycarbonate
Driver / Ballast	LED Dali Driver - Xitanium, 41W, 0.5-0.8A, 51V G2
Lamp(s)	Dual LED strip module, 3,000K warm white, 5,700K cool white, 50,000h life [L70/B50 Ta 40°C], Ra>80
Operating Voltage	240V AC; 50Hz
Power Factor	0.9 @ default
Supply Current	180mA +/- 20mA
Inrush Current (Max)	15.8A @ 288µs
Earth Leakage	0.037-0.047mA
Total lumen output	4608lm (123.5lm/W) @default (refer to table on next page for details)
Power Consumption	37.3W @default (refer to table on next page for details)
IP Rating	IP65
IK Rating	IK08
Operating Temperature	0°C to 40°C
Impact Rating	IK08
Applicable Standards	AS/NZS3820, CISPR15, AS/NZS60598.1
Compliance Marking (RCM)	



ARGO-1200-DD

Argo 1200mm Weatherproof Batten,
Switchable Colour, DALI Driver

REPLACEMENT PARTS

PART NUMBER	DESCRIPTION
N/A	BATTERY
8002682	LED Panel
1330111	240V Driver

The product details described in this document are current as at the version date of the document. We reserve the right to change product design, specifications or materials (Specifications) as part of our continuous improvement program. Please confirm the applicable Specifications at the time of placing your order

Power Consumption & Lumen Output	Output (700mA)	
	Lamp On	Lumen Output
3000K	38.5W	4190 lm
4000K Default	37.3W	4608 lm
5700K	38.4W	4350 lm