

ARGO-1200-SEN-LP-D2

Argo 1200mm Weatherproof Emergency Batten, LP, Switchable Colour, Motion Sensor, DALI-2



Part Number	ARGO-1200-SEN-LP-D2			
MIC	AUB02221680001			
Description	Argo 1200mm Weatherproof Emergency Batten, LP, Switchable Colour, Motion Sensor, DALI-2			
Construction	Polycarbonate Base and Diffuser with Captive Stainless-Steel Clips (SS301)			
Mounting	Surface mount			
Dimensions L x W x H	1265mm x 121mm x 88mm			
Weight	2.7 kg			
Operating Mode	Sustained			
Testing System	DALI-2			
Battery	Lithium Iron Phosphate, 3.2V 6400mAh			
Charging Method	Intelligent current limited constant voltage			
Diffuser	Polycarbonate			
Driver / Ballast	LED Driver - 40w Stallion, MS-HL			
Lamp(s)	Dual LED strip module, 3,000K warm white, 5,700K cool white, 50,000h life [L70/B50 Ta 40°C], Ra>80			
Operating Voltage	240V AC; 50Hz			
Power Factor	0.91 @ default			
Supply Current	167mA +/-20mA			
Total lumen output	4550lm (128lm/W @4000K), details see table Page 2			
Power Consumption	see table Page 2			
IP Rating	IP65			
Operating Temperature	0°C to 40°C			
Impact Rating	IK08			
AS2293 Classification	C ₀ =D63 C ₉₀ =D40			
Applicable Standards	AS/NZS3820, CISPR15, AS/NZS2293.3			
Compliance Marking (RCM)	<u>&</u>			





ARGO-1200-SEN-LP-D2

Argo 1200mm Weatherproof Emergency Batten, LP, Switchable Colour, Motion Sensor, DALI-2



REPLACEMENT PARTS				
PART NUMBER	DESCRIPTION			
1550230	Battery			
AUM02270540001 CLIFE-PRO-CKIT-D2-NP	Driver Pack			
8003062	DALI-2 Node			
1330082	LED Driver			
8002700	LED Strip			
8002681 x2	240V LED Strip			

		Total Lumen				
Colour	MAX Charge	Standby	Standby	Standby	Output	
	Lamp ON	Lamp ON	Lamp MIN (10%)	Lamp OFF	Output	
3000K	42 W	40 W	6 W	0.7 W	3819 lm	
4000K	40 W	37 W	6 W	0.7 W	4318 lm	
5700K	42 W	40 W	6 W	0.7 W	4100 lm	

The product details described in this document are current as at the version date of the document. We reserve the right to change product design, specifications or materials (Specifications) as part of our continuous improvement program. Please confirm the applicable Specifications at the time of placing your order

