

ARGO-1200-SEN-LP-DALI

Argo 1200mm Weatherproof Emergency Batten, LP, Switchable Colour, Motion Sensor, DALI Emergency



PRODUCT INFORMATION	l			
Part Number	ARGO-1200-SEN-LP-DALI			
MIC	AUB02221240003			
Description	Argo 1200mm Weatherproof Emergency Batten, LP, Switchable Colour, Motion Sensor, DALI Emergency			
Construction	Polycarbonate Base and Diffuser with Captive Stainless-Steel Clips (SS301)			
Mounting	Surface mount			
Dimensions L x W x H	1265mm x 121mm x 88mm			
Weight	2.7 kg			
Operating Mode	Sustained			
Testing System	DALI Registered			
Battery	Lithium Iron Phosphate, 3.2V 6400mAh			
Charging Method	Intelligent current limited constant voltage			
Diffuser	Polycarbonate			
Driver / Ballast	LED Driver - 40w Stallion, MS-HL			
Lamp(s)	Dual LED strip module, 3,000K warm white, 5,700K cool white, 50,000h life [L70/B50 Ta 40°C], Ra>80			
Operating Voltage	240V AC; 50Hz			
Power Factor	0.91 @ default			
Supply Current	167mA +/-20mA			
Total lumen output	4550lm (128lm/W @4000K, based on non-emergency), details see table Page			
Power Consumption	see table Page 2			
IP Rating	IP65			
Operating Temperature	0°C to 40°C			
Impact Rating	IK08			
AS2293 Classification	C ₀ =D63 C ₉₀ =D40			
Applicable Standards	AS/NZS3820, CISPR15, AS/NZS2293.3			
Compliance Marking (RCM)	<u>&</u>			





ARGO-1200-SEN-LP-DALI

Argo 1200mm Weatherproof Emergency Batten, LP, Switchable Colour, Motion Sensor, DALI Emergency



REPLACEMENT PARTS				
PART NUMBER	DESCRIPTION			
1550230	Battery			
AUM02270220002 CLIFE-PRO-CKIT-DALI-NP	Driver Pack			
8003060	DALI Node			
1330082	240V Driver			
8002700	LED Strip			
8002681	240V LED Strip			

Colour		Total Lumen			
	MAX Charge	Standby	Standby	Standby	Output
	Lamp ON	Lamp ON	Lamp MIN (10%)	Lamp OFF	
3000K	42 W	40 W	3 W	0.7 W	4212 lm
4000K	40 W	37 W	3 W	0.7 W	4550 lm
5700K	42 W	40 W	3 W	0.7 W	4296 lm

The product details described in this document are current as at the version date of the document. We reserve the right to change product design, specifications or materials (Specifications) as part of our continuous improvement program. Please confirm the applicable Specifications at the time of placing your order

