

ARGO-1200-SEN-LP

CLEVERTRONICS LP ARGO LED WEATHERPROOF BATTEN WITH INTEGRAL BATTERY, MICROWAVE SENSOR AND SWITCHABLE COLOUR



Part Number	ARGO-1200-SEN-LP				
MIC	AUB02320480002				
Description	LP Premium ARGO 1200mm LED Weatherproof Emergency Batten with Integral Battery, Microwave Sensor (Hi/Lo) and Switchable Colour Enabled with Clevertest Plus				
Construction	Polycarbonate Base and Diffuser with Captive Stainless-Steel Clips (SS301)				
Mounting	Surface mount				
Dimensions L x W x H	1265mm x 121mm x 88mm				
Weight	2.7 kg				
Operating Mode	Sustained				
Testing System	Clevertest Plus Enabled (Not activated by default)				
Battery	Lithium Iron Phosphate, 3.2V 6400mAh				
Charging Method	Intelligent current limited constant voltage				
Diffuser	Polycarbonate				
Driver / Ballast	LED Driver - 40w Stallion, MS-HL				
Lamp(s)	Dual LED strip module, 3,000K warm white, 5,700K cool white, 50,000h life [L70/B50 Ta 40°C], Ra>80				
Operating Voltage	240V AC; 50Hz				
Power Factor	0.91 @ default				
Supply Current	167mA +/-20mA				
Total lumen output	4318lm (118lm/W @4000K, based on non-emergency), details see table Page				
Power Consumption	see table Page 2				
IP Rating	IP65				
Operating Temperature	0°C to 40°C				
Impact Rating	IK08				
AS2293 Classification	C ₀ =D63 C ₉₀ =D40				
Applicable Standards	AS/NZS3820, CISPR15, AS/NZS2293.3				
Compliance Marking (RCM)					





ARGO-1200-SEN-LP

CLEVERTRONICS LP ARGO LED WEATHERPROOF BATTEN WITH INTEGRAL BATTERY, MICROWAVE SENSOR AND SWITCHABLE COLOUR



REPLACEMENT PARTS				
PART NUMBER	DESCRIPTION			
1550230	BATT:LP 3.2V 6400mAh.200mm lead.Brkt.			
AUM02370050001 CLIFE-PRO-CKIT-NP	Lifelight Pro, Control Only, 530mm, NP, CTP, OWC			
1330082	LED Driver - 40w Stallion, MS-HL			
8002700	PCA:LED Strip 2S4P, Eco Argonaut (EM)			
8002681	PCA: LED Strip for ARGO-1200, HT10520-A1 (Qty 2)			

		Total Lumen			
Colour	MAX Charge	Standby	Standby	Standby	Output
	Lamp ON	Lamp ON	Lamp MIN (10%)	Lamp OFF	
3000K	42 W	39 W	3 W	0.4 W	3819 lm
4000K	39 W	37 W	3 W	0.4 W	4318 lm
5700K	42 W	39 W	3 W	0.4 W	4100 lm

The product details described in this document are current as at the version date of the document. We reserve the right to change product design, specifications or materials (Specifications) as part of our continuous improvement program. Please confirm the applicable Specifications at the time of placing your order

