



ARGO-1200-SEN

CLEVERTRONICS 240V ARGO LED WEATHERPROOF BATTEN
WITH MICROWAVE SENSOR AND SWITCHABLE COLOUR



PRODUCT INFORMATION

Part Number	ARGO-1200-SEN
MIC	AUB04620370002
Description	240V ARGO 1200mm LED Weatherproof Batten with Microwave Sensor (Hi/Lo) and Switchable Colour
Construction	Polycarbonate Base and Diffuser with Captive Stainless-Steel Clips (SS301)
Mounting	Surface mount
Dimensions L x W x H	1265mm x 121mm x 88mm
Weight	2.4 kg
Diffuser	Polycarbonate
Driver / Ballast	LED Driver - 40W Stallion, MS-HL2
Lamp(s)	Dual LED strip module, 3,000K warm white, 5,700K cool white, 50,000h life [L70/B50 Ta 40°C], Ra>80
Operating Voltage	240V AC; 50Hz
Power Factor	0.85
Supply Current	180mA +/- 20mA
Inrush Current (Max)	15.909A, 160µs
Earth Leakage	0.037-0.047mA
Total lumen output	4529lm (125.5lm/W) @default (refer to table on next page for details)
Power Consumption	36.1W @default (refer to table on next page for details)
IP Rating	IP65
Operating Temperature	0°C to 40°C
Impact Rating	IK08
Applicable Standards	AS/NZS3820, CISPR15, AS/NZS60598.1
Compliance Marking (RCM)	



ARGO-1200-SEN

CLEVERTRONICS 240V ARGO LED WEATHERPROOF BATTEN
WITH MICROWAVE SENSOR AND SWITCHABLE COLOUR



REPLACEMENT PARTS

PART NUMBER	DESCRIPTION
1330089	240V Driver
8002682 x2	240V LED Strip
1190134	Sensor

Power Consumption & Lumen Output	Output (700mA)		
	Lamp On	Lamp Min 10% (Sensor version only)	Lumen Output
3000K	38.84W	2.7W	4137 lm
4000K (DEFAULT)	36.79W	2.7W	4529 lm
5700K	38.18W	2.7W	4282 lm

*The projected value has been calculated by extrapolation of the LM80 data using the Energy Star Calculator

The product details described in this document are current as at the version date of the document. We reserve the right to change product design, specifications or materials (Specifications) as part of our continuous improvement program. Please confirm the applicable Specifications at the time of placing your order