



## ARGO-1500-LP-D2

Argo 1500mm Weatherproof Emergency Batten, LP,  
Switchable Colour, DALI-2 Emergency



PRODUCT INFORMATION	
Product Code	ARGO-1500-LP-D2
MIC	AUB00000007401
Description	Argo 1500mm Weatherproof Emergency Batten, LP, Switchable Colour, DALI-2 Emergency
Colour CCT	Switchable 3000K / 4000K (Default) / 5700K
Output Configuration	Fixed Single Output
Battery Configuration	Integral Battery
Construction	Polycarbonate Base, Polycarbonate Diffuser and Captive Stainless-Steel Clips (SS301)
Diffuser	Polycarbonate
Mounting	Surface Mount
Operating Mode	Sustained
Testing System	DALI Registered
Battery	Lithium Iron Phosphate, 3.2V 6400mAh
Charging Method	Intelligent Current Limited Constant Voltage
Sensor Capability	N/A
Dimensions LxWxH (mm)	1565x121x88
Weight (kg)	3.2
Driver / Ballast	LED Driver - Xitanium, 72w, 1.2-1.4A, 51V DS 230V
Lamp(s)*	LED strip module, 3000K / 5700K, Ra>80 L70/B50 Ta 40°C; LM80 Report >60,000hr, Projected 168,000hr L80/B20 Ta 40°C; LM80 Report >60,000hr, Projected 84,000hr L90/B10 Ta 40°C; LM80 Report 37,000hr, Projected 37,000hr
Supply Voltage	220-240V~ 50Hz
Power Factor	0.93@ Default
Supply Current	232mA +/- 20mA
Inrush Current (Peak/Duration)	35A<94µs
Earth Leakage	0.252mA
Total lumen output	6244lm (112.10lm/W) @ default (refer to next page for details)
Power Consumption	53.4W @ default (refer to next page for details)
Operating Temperature	0°C to 40°C
IP Rating	IP65
Impact Rating	IK08
LED MacAdam (SDCM)	5
AS2293 Classification	C0=D63 C90=D40
Applicable Standards	AS/NZS3820, CISPR15, AS/NZS2293.3
Compliance Marking	



## ARGO-1500-LP-D2

Argo 1500mm Weatherproof Emergency Batten, LP,  
Switchable Colour, DALI-2 Emergency

### REPLACEMENT PARTS

PART NUMBER	DESCRIPTION
1330108	240V Driver
8002851 x 2	240V LED Panel
AUM02270540002 CLIFE-PRO-CKIT-D2-NP	Emergency Driver Pack
8002700	Emergency LED Panel
1550230	Battery
N/A	Microwave Motion Sensor

Power Consumption & Lumen Output	Output 1200mA				
	MAX Charge Lamp ON	Standby Lamp ON	Lamp On, Min 10%	Standby Lamp OFF	Lumen Output
3000K	59.1W	56.8W	N/A	0.7W	5904lm
4000K	55.7W	53.4W	N/A	0.7W	6244lm
5700K	59.5W	56.8W	N/A	0.7W	5631lm

The product details described in this document are current as at the version date of the document. We reserve the right to change product design, specifications or materials (Specifications) as part of our continuous improvement program. Please confirm the applicable Specifications at the time of placing your order