



## ARGO-1500-SEN-LP-HV

CLEVERTRONICS Argo 1500mm Weatherproof Emergency Batten, LP, Switchable Colour, Motion Sensor, Zoneworks XT Hive



### PRODUCT INFORMATION

<b>Product Code</b>	ARGO-1500-SEN-LP-HV
<b>MIC</b>	AUB02820590001
<b>Description</b>	Argo 1500mm Weatherproof Emergency Batten, LP, Switchable Colour, Motion Sensor, Zoneworks XT Hive
<b>Colour CCT</b>	Switchable 3000K / 4000K (Default) / 5700K
<b>Output Configuration</b>	Fixed Single Output
<b>Battery Configuration</b>	Integral Battery
<b>Construction</b>	Polycarbonate Base, Polycarbonate Diffuser and Captive Stainless-Steel Clips (SS301)
<b>Diffuser</b>	Polycarbonate
<b>Mounting</b>	Surface Mount
<b>Operating Mode</b>	Sustained
<b>Testing System</b>	Zoneworks XT HIVE (RF)
<b>Battery</b>	Lithium Iron Phosphate, 3.2V 6400mAh
<b>Charging Method</b>	Intelligent Current Limited Constant Voltage
<b>Sensor Capability</b>	High/Low, On/Off, Master Slave Capable - Yes
<b>Dimensions LxWxH (mm)</b>	1565x121x88
<b>Weight (kg)</b>	3.3
<b>Driver / Ballast</b>	LED Driver - TCI DC MAXI JOLLY SVM 65 DALI SLIM
<b>Lamp(s)*</b>	LED strip module, 3000K / 5700K, Ra>80 L70/B50 Ta 40°C; LM80 Report >60,000hr, Projected 168,000hr L80/B20 Ta 40°C; LM80 Report >60,000hr, Projected 84,000hr L90/B10 Ta 40°C; LM80 Report 37,000hr, Projected 37,000hr
<b>Supply Voltage</b>	220-240V~ 50Hz
<b>Power Factor</b>	0.92 @ Default
<b>Supply Current</b>	250mA +/- 20mA
<b>Inrush Current (Max)</b>	17A<76μs
<b>Earth Leakage</b>	0.367mA
<b>Total lumen output</b>	6244lm (109.16lm/W) @ default (refer to next page for details)
<b>Power Consumption</b>	54.9W @ default (refer to next page for details)
<b>Operating Temperature</b>	0°C to 40°C
<b>IP Rating</b>	IP65
<b>Impact Rating</b>	IK08
<b>LED MacAdam Step (SDCM)</b>	5
<b>AS2293 Classification</b>	C0=D63 C90=D40
<b>Applicable Standards</b>	AS/NZS3820, CISPR15, AS/NZS2293.3
<b>Compliance Marking</b>	



## ARGO-1500-SEN-LP-HV

CLEVERTRONICS Argo 1500mm Weatherproof Emergency Batten, LP, Switchable Colour, Motion Sensor, Zoneworks XT Hive



### REPLACEMENT PARTS

PART NUMBER	DESCRIPTION
1330151	240V Driver
8002851	240V LED Panel
AUM02870110001 CLIFE-PRO-CKIT-HV-NP	Emergency Driver Pack
8002700	Emergency LED Panel
1550230	Battery
1190118	Microwave Motion Sensor

Power Consumption & Lumen Output	Output (1200mA)				
	Max Charge, Lamp On	Standby Charge, Lamp On	Standby Charge, Lamp Min. 10% (sensor version only)	Standby Charge, Lamp Off	Lumen Output
3000K	60.8W	58.5W	11.4W	0.7W	5904lm
4000K (DEFAULT)	57.2W	54.9W	11.2W	0.7W	6244lm
5700K	60.4W	58.1W	11.3W	0.7W	5631lm

\*The projected value has been calculated by extrapolation of the LM80 data using the Energy Star Calculator

The product details described in this document are current as at the version date of the document. We reserve the right to change product design, specifications, or materials (Specifications) as part of our continuous improvement program. Please confirm the applicable Specifications at the time of placing your order