



ARGO-1500-SEN

CLEVERTRONICS Argo 1500mm Weatherproof Batten, Switchable Colour, Motion Sensor



PRODUCT INFORMATION

Product Code	ARGO-1500-SEN
MIC	AUB04620490001
Description	Argo 1500mm Weatherproof Batten, Switchable Colour, Motion Sensor
Colour CCT	Switchable 3000K / 4000K (Default) / 5700K
Output Configuration	Fixed Single Output
Construction	Polycarbonate Base, Polycarbonate Diffuser and Captive Stainless-Steel Clips (SS301)
Diffuser	Polycarbonate
Mounting	Surface Mount
Sensor Capability	High/Low, On/Off, Master Slave Capable - Yes
Dimensions LxWxH (mm)	1565x121x88
Weight (kg)	2.8
Driver / Ballast	LED Driver - TCI DC MAXI JOLLY SVM 65 DALI SLIM
Lamp(s)*	LED strip module, 3000K / 5700K, Ra>80 L70/B50 Ta 40°C; LM80 Report >60,000hr, Projected 168,000hr L80/B20 Ta 40°C; LM80 Report >60,000hr, Projected 84,000hr L90/B10 Ta 40°C; LM80 Report 37,000hr, Projected 37,000hr
Supply Voltage	220-240V~ 50Hz
Power Factor	0.94 @ Default
Supply Current	240mA +/- 20mA
Inrush Current (Max)	16A<31μs
Earth Leakage	0.051mA
Total lumen output	6244lm (115.20lm/W) @ default (refer to next page for details)
Power Consumption	54.2W @ default (refer to next page for details)
Operating Temperature	0°C to 40°C
IP Rating	IP65
Impact Rating	IK08
LED MacAdam Step (SDCM)	5
Applicable Standards	AS/NZS3820, CISPR15, AS/NZS60598.1
Compliance Marking	



ARGO-1500-SEN

CLEVERTRONICS Argo 1500mm Weatherproof Batten, Switchable Colour, Motion Sensor



REPLACEMENT PARTS

COMPONENT	PART NUMBER & DESCRIPTION
1330151	240V Driver
8002851	240V LED Panel
1190118	Microwave Motion Sensor

Power Consumption & Lumen Output	Output (1200mA)		
	Lamp On	Lamp Min 10% (Sensor version only)	Lumen Output
3000K	57.8W	8.4W	5904lm
4000K (DEFAULT)	54.2W	8.2W	6244lm
5700K	57.4W	8.3W	5631lm

*The projected value has been calculated by extrapolation of the LM80 data using the Energy Star Calculator

The product details described in this document are current as at the version date of the document. We reserve the right to change product design, specifications, or materials (Specifications) as part of our continuous improvement program. Please confirm the applicable Specifications at the time of placing your order