



ARGOBUNKPRO-DD-BLK

Argonaut Bunkalite Pro, IP65 Weatherproof, DALI-2 Driver, Black



PRODUCT INFORMATION

| | |
|--------------------------------|--|
| Part Number | ARGOBUNKPRO-DD-BLK |
| MIC | UKB00000010301 |
| Description | Argonaut Bunkalite Pro, IP65 Weatherproof, DALI-2 Driver, Black |
| Product Construction | Die-cast Aluminium Body with Polycarbonate Diffuser |
| Mounting Method | Surface Mount |
| Colour Temperature | 4000K |
| Colour Rendering Index (CRI) | >80 |
| Colour Consistency | 3 SDCM |
| Total Lumen Output | 1945lm |
| Power Consumption | 17W |
| LED Rated Service Life | L70/B50 Ta 40°C: Reported >102,000h, Projected >270,000h L80/B20 Ta 40°C: Reported >100,000h, Projected >100,000h L90/B10 Ta 40°C: Reported >43,000h, Projected >43,000h |
| Ingress Protection (IP) | IP65 |
| Impact Resistant (IK) | IK10 |
| Operating Temperature | 0°C to 40°C |
| Operating Voltage | 220-240V~ 50Hz |
| Power factor | 0.9 |
| Supply Current | 71mA |
| Inrush Current (Peak/Duration) | 10.2A/106μs |
| Earth Leakage | 0.22mA |
| Dimensions | 145mm x 360mm (Diameter) |
| Weight | 4.3kg |
| Applicable Standards | BS EN IEC 60598-2-1, S EN IEC 55015, BS EN IEC 61547, BS EN IEC 61000-3-2, BS EN IEC 61000-3-3 |
| Compliance Marking | UK CA CE |

The product details described in this document are current as at the version date of the document. We reserve the right to change product design, specifications or materials (Specifications) as part of our continuous improvement program. Please confirm the applicable Specifications at the time of placing your order.