



## ARGOBUNKPRO-L10-HVG-BLK

Argonaut Bunkalite Pro, IP65 Weatherproof Emergency, L10, Zoneworks Hive, Black



### PRODUCT INFORMATION

|                                |                                                                                                                                                                                |
|--------------------------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Part Number                    | ARGOBUNKPRO-L10-HVG-BLK                                                                                                                                                        |
| MIC                            | UKB00000010601                                                                                                                                                                 |
| Description                    | Argonaut Bunkalite Pro IP65 Weatherproof, Emergency, L10 Nanophosphate, Sustained, Zoneworks Hive, Black                                                                       |
| Product Construction           | Die-cast Aluminium Body with Polycarbonate Diffuser                                                                                                                            |
| Mounting Method                | Surface Mount                                                                                                                                                                  |
| Colour Temperature             | 4000K                                                                                                                                                                          |
| Colour Rendering Index (CRI)   | >80                                                                                                                                                                            |
| Colour Consistency             | 3 SDCM                                                                                                                                                                         |
| Total Lumen Output             | 1945lm                                                                                                                                                                         |
| Power Consumption              | 21W (Lamps ON, Max Charge),<br>1.2W (Lamp OFF, Standby)                                                                                                                        |
| LED Rated Service Life         | L70/B50 Ta 40°C: Reported >102,000h, Projected >270,000h<br>L80/B20 Ta 40°C: Reported >100,000h, Projected >100,000h<br>L90/B10 Ta 40°C: Reported >43,000h, Projected >43,000h |
| Sensor Capability              | N/A                                                                                                                                                                            |
| Emergency Operating Mode       | Sustained                                                                                                                                                                      |
| Emergency Testing System       | Zonework Hive (RF) 2.4GHz                                                                                                                                                      |
| Emergency Lumen Output         | 390lm                                                                                                                                                                          |
| Battery                        | Lithium Nanophosphate (LiFePO4)                                                                                                                                                |
| Battery Charging Method        | Intelligent Current Limited Constant Voltage                                                                                                                                   |
| Luminaire Classification       | X   2   ADF   180                                                                                                                                                              |
| Ingress Protection (IP)        | IP65                                                                                                                                                                           |
| Impact Resistant (IK)          | IK10                                                                                                                                                                           |
| Operating Temperature          | 0°C to 40°C                                                                                                                                                                    |
| Operating Voltage              | 220-240V~ 50Hz                                                                                                                                                                 |
| Power factor                   | 0.9                                                                                                                                                                            |
| Supply Current                 | 86mA                                                                                                                                                                           |
| Inrush Current (Peak/Duration) | 10.2A/106μs                                                                                                                                                                    |
| Earth Leakage                  | 0.02mA                                                                                                                                                                         |
| Dimensions                     | 145mm x 360mm (Diameter)                                                                                                                                                       |
| Weight                         | 4.5kg                                                                                                                                                                          |
| Applicable Standards           | BS 5266-1, BS EN IEC 60598-2-22, BS EN IEC 55015, BS EN IEC 61547, BS EN IEC 61000-3-2, BS EN IEC 61000-3-3, ETSI EN 301 489-1, ETSI EN 301 489-17                             |
| Compliance Marking             |                                                                                                                                                                                |

The product details described in this document are current as at the version date of the document. We reserve the right to change product design, specifications or materials (Specifications) as part of our continuous improvement program. Please confirm the applicable Specifications at the time of placing your order.