

ARGOCIRC-SEN-EM-WHT

Argo Circular Emergency, Trade Series, Switchable Colour, Motion Sensor, White



PRODUCT INFORMATION				
Part Number	ARGOCIRC-SEN-EM-WHT			
MIC	AUC03520040001			
Description	Argo Circular Emergency, Trade Series, Switchable Colour, Motion Sensor, White			
Colour CCT	Switchable 3000K / 4000K (Default) / 5700K			
Switchable output	High (Default) / Low			
Material	Base & Diffuser: Polycarbonate			
Mounting	Ceiling/Wall Surface Mount			
Sensor Capability	Microwave, High/Low, Master Slave - No			
Dimensions	Ø 330mm x 84mm			
Weight	1.52kg			
Operating Mode	SUSTAINED			
Testing System	N/A			
Battery	Lithium Iron Phosphate, 3.2V 3000mAh			
Charging Method	Intelligent Current Limited Constant Voltage			
Driver	26W Stallion, 28-56VDC, MS-HL2, 366mA			
Lamp(s)	Dual LED panel, 3,000K warm white, 4,000K natural white, 5,700K cool white, Ra>80 L70/B50 Ta 25°C; LM80 Report >102k Hours, Projected >275k Hours L70/B50 Ta 40°C; LM80 Report >102k Hours, Projected >270k Hours L80/B20 Ta 40°C; LM80 Report >100k Hours, Projected >100k Hours L90/B10 Ta 40°C; LM80 Report >43k Hours, Projected >43k Hours			
Operating Voltage	220-240V~ 50Hz			
Total Lumen Output	2034 lm (124.0lm/W) @default (refer to next page for details)			
Power Consumption	17.3W @default (refer to next page for details)			
Supply Current	0.083+/-20mA			
Inrush Current (Peak/Duration)	26.70Α / 100 μs			
Earth Leakage				
IP Rating	IP65			
IK Rating	IK08			
LED MacAdam	5			
Operating Temperature	0 °C to 40°C			
AS2293 Classification	C0=D40 C90=D40			
Applicable Standards	AS/NZS3820, AS/NZ60598-2-22, CISPR15, AS/NZS2293.3			
Appliance Class	Class II double insulated			
Compliance Marking				





ARGOCIRC-SEN-EM-WHT Argo Circular Emergency, Trade Series, Switchable Colour, Motion Sensor, White

REPLACEMENT PARTS		
PART NUMBER	DESCRIPTION	
1560150	Battery	
1330104	240V Driver	
805-00002	240V LED Panel	
AUM03570050001	Emergency Driver	
1190134	Sensor	

Power Consumption _ & Lumen Output	Output (500mA)					
	MAX Charge Lamp ON	Standby Lamp ON	Lamp On, Min 10%	Standby Lamp OFF	Lumen Output	
3000К	17.7W	16.8W	3.4W	0.4W	1966 lm	
4000K	17.3W	16.4W	3.4W	0.4W	2034 lm	
5700K	17.8W	16.9W	3.4W	0.4W	2030 lm	

The product details described in this document are current as at the version date of the document. We reserve the right to change product design, specifications or materials (Specifications) as part of our continuous improvement program. Please confirm the applicable Specifications at the time of placing your order

