



ARGOCIRCPRO-DD-WHT

Argo Circular Pro, IP65 Weatherproof, Mains, Switchable Colour & Output, DALI-2 Driver, White



PRODUCT INFORMATION

Part Number	ARGOCIRCPRO-DD-WHT
MIC	UKB00000004301
Description	Argo Circular Pro, IP65 Weatherproof, Mains, Switchable Colour & Output, DALI-2 Driver, White
Mounting Method	Ceiling/Wall Surface Mount
Colour Temperature	Switchable 3000K / 4000K (Default) / 5700K
Colour Rendering Index (CRI)	>80
Colour Consistency	3 SDCM
Total Lumen Output	2034lm (refer to the below table)
Power Consumption	16.1W (refer to the below table)
LED Rated Service Life	L70/B50 Ta 40°C: Reported >102,000h, Projected >270,000h L80/B20 Ta 40°C: Reported >100,000h, Projected >100,000h L90/B10 Ta 40°C: Reported >43,000h, Projected >43,000h
Ingress Protection (IP)	IP65
Impact Resistant (IK)	IK08
Protection Class	<input checked="" type="checkbox"/> Class II double insulated
Operating Temperature	0°C to 40°C
Operating Voltage	220-240V~ 50Hz
Power factor	0.88 @ default
Supply Current	0.075mA
Inrush Current (Peak/Duration)	15.50A / 73µs
Earth Leakage	N/A
Dimensions	84mm x 330mm
Weight	1.3kg
Applicable Standards	BS EN IEC 60598-2-1, BS EN IEC 55015, BS EN IEC 61547, BS EN IEC 61000-3-2, BS EN IEC 61000-3-3
Compliance Marking	

Power Consumption & Lumen Output		
	Lamp On	Lumen Output
3000K	16.5W	1966 lm
4000K (DEFAULT)	16.1W	2034 lm
5700K	16.5W	2030 lm

The product details described in this document are current as at the version date of the document. We reserve the right to change product design, specifications or materials (Specifications) as part of our continuous improvement program. Please confirm the applicable Specifications at the time of placing your order.