



## ARGOPLUS-1200-SEN-LP-HVG

Argonaut Plus 1200mm Weatherproof Emergency Batten, CLP, Switchable Colour, Motion Sensor, Zoneworks XT Hive



PRODUCT INFORMATION	
Product Code	ARGOPLUS-1200-SEN-LP-HVG
MIC	UKB02820640002
Description	Argonaut Plus 1200mm Weatherproof Emergency Batten, CLP, Switchable Colour, Motion Sensor, Zoneworks Hive
Colour CCT	Switchable 3000K / 4000K (Default) / 5700K
Material	Polycarbonate Base and Diffuser w/Stainless Steel Clips (SS304)
Mounting	Surface Mount
Sensor Capability	High/Low, On/Off, Master Slave Capable - No
Dimensions LxWxH (mm)	1265 x 160 x 105
Weight (kg)	2.9
Operating Mode	SUSTAINED
Testing System	Zoneworks XT HIVE (RF)
Battery	Lithium Iron Phosphate, 3.2V 6400mAh
Operating Voltage	220-240V~ 50Hz
Charging Method	Intelligent current limited constant voltage
Driver	LED Driver - 40w Stallion, MS-HL, 650mA
Power Factor	0.91 @ default
Power Consumption	33.5W @ default (refer to next page for details)
Supply Current	170mA +/-20mA
Inrush Current (Max)	47.1A<800µs
Earth Leakage	0.42mA
Lamp(s)*	LED strip module, 3000K / 5700K, Ra>80 L70/B50 Ta 40°C; LM80 Report >60,000hr, Projected 157,000hr L80/B20 Ta 40°C; LM80 Report >60,000hr, Projected 95,000hr L90/B10 Ta 40°C; LM80 Report 43,000hr, Projected 43,000hr
Total lumen output	4420lm (132 lm/W) @ default (refer to next page for details)
Emergency Lumens	396lm
Operating Temperature	0°C to 40°C
IP Rating	IP65
Impact Rating	IK08
LED MacAdam Step (SDCM)	4
Rated Emergency Duration	180 minutes
Luminaire Classification	X   2   ADF   180
Conformity	BS IEC 60598-2-22, BS 5266, BS EN IEC 55015, BS EN 61547, BS EN IEC 61000-3-2
Compliance Marking	UK   CE



## ARGOPLUS-1200-SEN-LP-HVG

Argonaut Plus 1200mm Weatherproof Emergency Batten,  
CLP, Switchable Colour, Motion Sensor, Zoneworks XT Hive

### REPLACEMENT PARTS

PART NUMBER	DESCRIPTION
1553230	Battery
8002752 x 1	240V LED Strip
1330093	240V Driver
8003110 x 2	Emergency LED Strip
UKM02870030003 CLIFE-PRO-CKIT-HVG-475	Emergency Driver
8003330	HIVE Node
1190134	Sensor

Power Consumption & Lumen Output	Output (650mA)				
	MAX Charge Lamp ON	Standby Lamp ON	Lamp On, Min 10%	Standby Lamp OFF	Lumen Output
3000K	36.9W	34.6W	5.5W	0.7W	4145 lm
4000K (DEFAULT)	35.8W	33.5W	5.2W	0.7W	4420 lm
5700K	36.7W	34.4W	5.4W	0.7W	4322 lm

The product details described in this document are current as at the version date of the document. We reserve the right to change product design, specifications or materials (Specifications) as part of our continuous improvement program. Please confirm the applicable Specifications at the time of placing your order