



## ARGOPLUS-600-DD-L10POD-DALI

CLEVERTRONICS Argonaut Plus 600mm Weatherproof Emergency Batten, L10  
with POD, Switchable Colour, DALI Driver, DALI Emergency



### PRODUCT INFORMATION

Product Code	ARGOPLUS-600-DD-L10POD-DALI
MIC	UKB01220180002
Description	Argonaut Plus 600mm Weatherproof Emergency Batten, L10 with POD, Switchable Colour, DALI Driver, DALI Emergency
Colour CCT	Switchable 3000K / 4000K (Default) / 5700K
Output Configuration	Fixed Single Output
Battery Configuration	Batteries contained within thermally isolated POD for optimum battery life
Construction	Polycarbonate Base and Diffuser w/Stainless Steel Clips (SS304)
Diffuser	Polycarbonate
Mounting	Surface Mount
Operating Mode	SUSTAINED
Testing System	DALI Registered
Battery	Lithium Nanophosphate, 3.3V 5000mAh
Charging Method	Intelligent current limited constant voltage
Sensor Capability	n/a
Dimensions LxWxH (mm)	720x160x105
Weight (kg)	2.0
Driver / Ballast	LED DALI Driver - 25W, 350-1050mA, 20-50V, one4all
Lamp(s)*	LED strip module, 3000K / 5700K, Ra>80 L70/B50 Ta 40°C; LM80 Report >60,000hr, Projected 157,000hr L80/B20 Ta 40°C; LM80 Report >60,000hr, Projected 95,000hr L90/B10 Ta 40°C; LM80 Report 43,000hr, Projected 43,000hr
Supply Voltage	220-240V~ 50Hz
Power Factor	0.86 @ default
Supply Current	105mA +/-20mA
Inrush Current (Max)	46.2A<500µs
Earth Leakage	0.5mA
Total lumen output	2351 lm (131 lm/W) @ default (refer to next page for details)
Power Consumption	18.0W @ default (refer to next page for details)
Operating Temperature	0°C to 40°C
IP Rating	IP65
Impact Rating	IK08
LED MacAdam Step (SDCM)	4
Rated Emergency Duration	180 minutes
Emergency Lumens	333
Compliance Marking	UK CA   CE



## ARGOPLUS-600-DD-L10POD-DALI

CLEVERTRONICS Argonaut Plus 600mm Weatherproof Emergency Batten, L10  
with POD, Switchable Colour, DALI Driver, DALI Emergency



### PRODUCT INFORMATION

Protection	<ul style="list-style-type: none"><li>• Battery overvoltage &amp; overcurrent protection</li><li>• Battery deep discharge protection</li><li>• Supply voltage polarity reversal protection</li><li>• Battery short-circuit protection (charging will resume upon removal of fault)</li><li>• Kit box (enclosure) of lamp controlgear provides protection against accidental contacts with live parts</li></ul>			
Luminaire Classification	X	2	ADF	180
Conformity	BS IEC 60598-2-22, BS 5266, BS EN IEC 55015, BS EN 61547, BS EN IEC 61000-3-2			

### REPLACEMENT PARTS

COMPONENT	PART NUMBER & DESCRIPTION
240V Driver	1330038 - LED DALI Driver - 25W, 350-1050mA, 20-50V, one4all
240V LED Strip	8002751 - PCA:LED Strip ARGOPUS-600,8P8S,3000K/5700K
Emergency Driver	UKM01270060002 - Lifelight Pro, Control Only, Dali Reg, L10, 415mA
Emergency LED Strip	8050205 - HWSUB: CT10570-A4 - 2 LED WHITE
Battery	1530050 - BATTERY:L10 3.3V 2.5AH 70mm lead, no Brkt
Sensor	n/a

Power Consumption & Lumen Output	Output (700mA)				
	Max Charge, Lamp On	Standby Charge, Lamp On	Standby Charge, Lamp Min. 10% (sensor version only)	Standby Charge, Lamp Off	Lumen Output
3000K	20.8W	18.5W	n/a	0.7W	2192 lm
4000K (DEFAULT)	20.3W	18.0W	n/a	0.7W	2351 lm
5700K	20.8W	18.5W	n/a	0.7W	2304 lm

\*The projected value has been calculated by extrapolation of the LM80 data using the Energy Star Calculator

The product details described in this document are current as at the version date of the document. We reserve the right to change product design, specifications or materials (Specifications) as part of our continuous improvement program. Please confirm the applicable Specifications at the time of placing your order