



ARGOPRO-1200-CC-SEN

Argonaut Pro 1200mm Weatherproof Batten, Configurable Output,
Combine Control, Motion Sensor



PRODUCT INFORMATION

Product Code	ARGOPRO-1200-CC-SEN
MIC	AUB04621060002
Description	Argonaut Pro 1200mm Weatherproof Batten, Configurable Output, Combine Control, Motion Sensor
Colour CCT	4000K
Output Configuration	Configurable Quad Output
Construction	Polycarbonate Base and Diffuser w/Stainless Steel Clips (SS316)
Diffuser	Polycarbonate
Mounting	Surface Mount
Sensor Capability	High/Low, On/Off, Combine Control
Dimensions LxWxH (mm)	1265x160x105
Weight (kg)	2.7
Driver / Ballast	LED Driver - 50w Mustang PRO, Combine Control
Lamp(s)*	LED strip module, 4000K, Ra>80 L70/B50 Ta 40°C; LM80 Report >60,000hr, Projected 184,000hr L80/B20 Ta 40°C; LM80 Report >60,000hr, Projected 100,000hr L90/B10 Ta 40°C; LM80 Report 43,000hr, Projected 43,000hr
Supply Voltage	220-240V~ 50Hz
Power Factor	0.93 @ default
Supply Current	198mA +/-20mA
Inrush Current (Max)	11.9A<1300µs
Earth Leakage	0.042mA
Total Lumen Output	4660 lm (151 lm/W) @ default (refer to next page for details)
Power Consumption	30.9W @ default (refer to next page for details)
Operating Temperature	0°C to 40°C
IP Rating	IP65
Impact Rating	IK08
LED MacAdam Step (SDCM)	3
Applicable Standards	AS/NZS3820, CISPR15, AS/NZS60598.1, EN 60598-2-1, BS EN IEC 55015, BS EN 61547, BS EN IEC 61000-3-2
Compliance Marking	



ARGOPRO-1200-CC-SEN

Argonaut Pro 1200mm Weatherproof Batten, Configurable Output, Combine Control, Motion Sensor



REPLACEMENT PARTS

COMPONENT	PART NUMBER & DESCRIPTION
Driver	133-00001 -LED Driver - 50w Mustang PRO, Combine Control
240V LED Strip	8002755 - PCA:LED Strip ARGOPRO-1200,HT10540-A1,16P16S,4000K
Sensor	1190132 - SENSOR: Microwave Motion Head Only
Node	800-00007 Combine Control V5 2.4GHz CT10816-A1 Int Ant Horiz

Power Consumption & Lumen Output	Lamp On	Lamp Min. 10% (sensor version only)	Lumen Output
Output 4 (900mA)	42.7W	5.3W	6259 lm
Output 3 (750mA)	36.3W	4.8W	5495 lm
Output 2 (650mA) DEFAULT	30.9W	4.0W	4660 lm
Output 1 (500mA)	24.1W	3.2W	3541 lm

*The projected value has been calculated by extrapolation of the LM80 data using the Energy Star Calculator

The product details described in this document are current as at the version date of the document. We reserve the right to change product design, specifications or materials (Specifications) as part of our continuous improvement program. Please confirm the applicable Specifications at the time of placing your order