



ARGOPRO-1200-L10

Argonaut Pro, 1200mm IP65 Weatherproof Batten, Mains, DALI-2 Driver, Configurable Output



PRODUCT INFORMATION	
Part Number	ARGOPRO-1200-DD
MIC	UKB01320210001
Description	Argonaut Pro, 1200mm IP65 Weatherproof Batten, Mains, DALI-2 Driver, Configurable Output
Product Construction	Polycarbonate Base & Diffuser w/ Stainless Steel Clips (SS316)
Mounting Method	Surface Mount
Colour Temperature	4000K
Colour Rendering Index (CRI)	>80
Colour Consistency	3 SDCM
Total Lumen Output	4660lm (refer to the table below for details)
Power Consumption	31.2W (refer to the table below for details)
LED Rated Service Life	L70/B50 Ta 40°C: Reported > 102,000h, Projected 275,000h L80/B20 Ta 40°C: Reported 100,000h, Projected 100,000h L90/B10 Ta 40°C: Reported 43,000h, Projected 43,000h
Sensor Capability	N/A
Ingress Protection (IP)	IP65
Impact Resistant (IK)	IK08
Operating Temperature	0°C to 40°C
Operating Voltage	220-240V~ 50Hz
Power factor	0.95 @ default
Supply Current	195mA +/-20mA
Inrush Current (Peak/Duration)	53.6A<800µs
Earth Leakage	0.31mA
Dimensions L x W x H	1265mm x 160mm x 105mm
Weight	2.7kg
Applicable Standards	EN 60598-2-1, BS EN IEC 55015, BS EN 61547, BS EN IEC 61000-3-2
Compliance Marking	

Power Consumption & Lumen Output	Lamp On	Lumen Output
Output 4 (900mA)	42.8W	6259lm
Output 3 (750mA)	37.1W	5495lm
Output 2 (600mA) DEFAULT	31.2W	4660lm
Output 1 (500mA)	24.5W	3541lm

The product details described in this document are current as at the version date of the document. We reserve the right to change product design, specifications or materials (Specifications) as part of our continuous improvement program. Please confirm the applicable Specifications at the time of placing your order.