



ARGOPRO-1500-CC-SEN-L10POD-HVG

Argonaut Pro 1500mm Weatherproof Emergency Batten, L10 Nanophosphate with POD, Configurable Output, Combine Control, Motion Sensor, Zoneworks HIVE



PRODUCT INFORMATION	
Product Code	ARGOPRO-1500-CC-SEN-L10POD-HVG
MIC	AUB00000005903
Product Description	Argonaut Pro 1500mm Weatherproof Emergency Batten, L10 Nanophosphate with POD, Configurable Output, Combine Control, Motion Sensor, Zoneworks HIVE
Mounting Method	Surface Mount/Suspension
Product Construction ¹	Recyclable UV Stabilised Polycarbonate (PC) Base with Stainless Steel Clips (SS316)
Diffuser Material	Recyclable UV Stabilised Polycarbonate (PC)
UL Flammability Rating	UL94 - V2 Self-extinguishing Polycarbonate (PC)
Halogen Free	Yes
Dimensions L x W x H	1630mm x 160mm x 105mm
Weight	3.9kg
Ingress Protection (IP) Rating	IP65
Impact Protection (IK) Rating ²	IK08
Operating Temperature	0°C to 40°C
Supply Voltage	220-240V~ 50Hz
Power Factor	0.94 @ default
Supply Current	276mA +/-20mA
Inrush Current (Max)	11.80A<1300µs
Earth Leakage	0.42mA

GENERAL LIGHTING - SPECIFICATION	
Colour Temperature	4000K
Colour Rendering Index (CRI)	≥ 90 (R9 > 50)
LED Colour Consistency	3 SDCM
Short Term Light Modulation (PstLM)	≤ 1.0
Stroboscopic Visibility Measure (SVM)	≤ 0.4
Flicker Free ³	Yes
Luminaire Output Configuration	Configurable Dual Output
Total Lumen Output	8498 lm (145.3 lm/W) @ default (refer to next page for details)
Power Consumption	58.5W@ default (refer to next page for details)
Rated LED lifetime ⁴	L70/B50 Ta 40 °C: Reported > 120,000h, Projected 219,500h L80/B20 Ta 40 °C: Reported 101,000h, Projected 101,000h L90/B10 Ta 40 °C: Reported 46,000h, Projected 46,000h
Driver ⁵	LED Driver - TCI DC MAXI JOLLY SVM 65 DALI SLIM
Sensor Capability	Microwave Sensor - High/Low, On/Off, Combine Control




ARGOPRO-1500-CC-SEN-L10POD-HVG

Argonaut Pro 1500mm Weatherproof Emergency Batten, L10
Nanophosphate with POD, Configurable Output, Combine Control,
Motion Sensor, Zoneworks HIVE

EMERGENCY LIGHTING - SPECIFICATION	
Emergency Operating Mode	Sustained
Emergency Testing System	Zoneworks HIVE (RF) 2.4GHz
Battery	Lithium Nanophosphate, 3.3V 5000mAh
Battery Configuration	Contained within Thermally Isolated POD for Optimum Battery Life
Battery Charging Method	Intelligent Current Limited Constant Voltage
AS/NZS 2293 Classification	C0=D80 C90=D80

PRODUCT INFORMATION - COMPLIANCE	
Green Building Schemes ⁶	Compliant with Green Star Flicker, CRI and MacAdam/SDCM Requirements
Applicable Standards	AS/NZS 3820, AS CISPR 15, AS/NZS 2293.3, AS 60598.2.22
Compliance Marking (RCM)	

REPLACEMENT PARTS	
Part Number	Description
1330151	240V Driver
AUM01970050002	Emergency Driver
801-00125	240V LED Strip
1530050	Battery
1190118	Sensor



Power Consumption & Lumen Output	Max Charge, Lamp On	Standby Charge, Lamp On	Standby Charge, Lamp Min. 10%	Standby Charge, Lamp Off	Lumen Output
Output 2 (1200mA) Default	61.9W	58.5W	7.4W	0.7W	8498 lm
Output 1 (900mA)	45.7W	43.4W	6.0W	0.7W	6358 lm

¹ All plastic materials will degrade under UV exposure over time, resulting in potential yellowing and surface degradation. UV stabilised materials are generally suited to indoor or sheltered environments with indirect UV exposure, while UL 746C – F1 rated UV resistant materials are suitable for outdoor applications with direct exposure to UV and moisture, providing enhanced resistance and reducing the rate of UV-induced ageing.

² When luminaire is ceiling mounted using appropriate fixings in accordance with the product instruction.

³ An LED luminaire is considered flicker-free if the SVM value is ≤ 0.4 and PstLM value is ≤ 1.0 .

⁴ The projected value has been calculated by extrapolation of the LM80 data using the Energy Star Calculator.

⁵ Products fitted with the Mustang Pro combo driver have two active (mains-230V) connections. All operating current is supplied via Lem (Permanent Active, unswitched) only and shall be sized accordingly. Lsw (Switched Active, control only) is a mains-voltage control line and carries no load.

⁶ Designed to meet the applicable building scheme requirements at the document version date. For full details, refer to the relevant building scheme specification.

The product details described in this document are current as at the version date of the document. We reserve the right to change product design, specifications or materials (Specifications) as part of our continuous improvement program. Please confirm the applicable Specifications at the time of placing your order.