



ARGOPRO-1500-DD-LP-HVG

Argonaut Pro 1500mm Weatherproof Emergency Batten, LP, DALI Driver, Zoneworks XT Hive



PRODUCT INFORMATION	
Part Number	ARGOPRO-1500-DD-LP-HVG
MIC	AUB02920710001
Description	Argonaut Pro 1500mm Weatherproof Emergency Batten, LP, DALI Driver, Zoneworks XT Hive
Colour CCT	4000K
Output Configuration	Configurable Dual Output
Battery Configuration	Integral Battery
Construction	Polycarbonate Base and Diffuser w/Stainless Steel Clips (SS316)
Diffuser	Polycarbonate
Mounting	Surface Mount
Operating Mode	SUSTAINED
Testing System	Zoneworks XT HIVE (RF), 2.4GHz
Battery	Lithium Iron Phosphate, 3.2V 6400mAh
Charging Method	Intelligent current limited constant voltage
Sensor Capability	n/a
Dimensions LxWxH (mm)	1565x160x105
Weight (kg)	3.6
Driver / Ballast	LED Driver - Tridonic LCA 75W 900-1800mA one4all lp PRE
Lamp(s)*	LED strip module, 4000K, Ra>80 L70/B50 Ta 40°C; LM80 Report >60,000hr, Projected 184,000hr L80/B20 Ta 40°C; LM80 Report >60,000hr, Projected 100,000hr L90/B10 Ta 40°C; LM80 Report 43,000hr, Projected 43,000hr
Supply Voltage	220-240V~ 50Hz
Power Factor	0.96 @ default
Supply Current	279mA +/-20mA
Inrush Current (Max)	47.9A<800µs
Earth Leakage	0.566mA
Total Lumen Output	8498 lm (143 lm/W) @ default (refer to next page for details)
Power Consumption	59.4W@ default (refer to next page for details)
Operating Temperature	0°C to 40°C
IP Rating	IP65
Impact Rating	IK08
LED MacAdam Step (SDCM)	3
AS2293 Classification	C0=D63 C90=D40
Applicable Standards	AS/NZS3820, CISPR15, AS/NZS2293.3
Compliance Marking (RCM)	



ARGOPRO-1500-DD-LP-HVG

Argonaut Pro 1500mm Weatherproof Emergency Batten, LP,
DALI Driver, Zoneworks XT Hive

REPLACEMENT PARTS

PART NUMBER	DESCRIPTION
1550230	Battery
8002756	240V LED Panel
8003110	Emergency LED Strip
1330073	240V Driver
AUM02870110002 CLIFE-PRO-CKIT-HV-NP	Emergency Driver
N/A	Sensor

Power Consumption & Lumen Output	MAX Charge Lamp ON	Standby Lamp ON	Lamp On, Min 10%	Standby Lamp OFF	Lumen Output
Output 2 DEFAULT (1200mA)	61.7W	59.4W	n/a	0.7W	8498 lm
Output 1 (900mA)	46.7W	44.4W	n/a	0.7W	6358 lm

The product details described in this document are current as at the version date of the document. We reserve the right to change product design, specifications or materials (Specifications) as part of our continuous improvement program. Please confirm the applicable Specifications at the time of placing your order