



ARGOPRO-1500

Argonaut Pro, 1500mm IP65 Weatherproof Batten, Mains, Configurable Output



PRODUCT INFORMATION	
Part Number	ARGOPRO-1500
MIC	UKB04620340001
Description	Argonaut Pro, 1500mm IP65 Weatherproof Batten, Mains, Configurable Output
Product Construction	Polycarbonate Base & Diffuser w/ Stainless Steel Clips (SS316)
Mounting Method	Surface Mount
Colour Temperature	4000K
Colour Rendering Index (CRI)	>80
Colour Consistency	3 SDCM
Total Lumen Output	8498lm (refer to the table below for details)
Power Consumption	58.1W (refer to the table below for details)
LED Rated Service Life	L70/B50 Ta 40°C: Reported > 102,000h, Projected 275,000h L80/B20 Ta 40°C: Reported 100,000h, Projected 100,000h L90/B10 Ta 40°C: Reported 43,000h, Projected 43,000h
Sensor Capability	N/A
Ingress Protection (IP)	IP65
Impact Resistant (IK)	IK08
Operating Temperature	0°C to 40°C
Operating Voltage	220-240V~ 50Hz
Power factor	0.97 @ default
Supply Current	255mA +/-20mA
Inrush Current (Peak/Duration)	35A<240µs
Earth Leakage	0.16mA
Dimensions L x W x H	1565mm x 160mm x 105mm
Weight	3.3kg
Applicable Standards	EN 60598-2-1, BS EN IEC 55015, BS EN 61547, BS EN IEC 61000-3-2
Compliance Marking	

Power Consumption & Lumen Output	Lamp On	Lumen Output
Output 4 (1200mA) DEFAULT	58.1W	8498lm
Output 3 (900mA)	42.8W	6358lm

The product details described in this document are current as at the version date of the document. We reserve the right to change product design, specifications or materials (Specifications) as part of our continuous improvement program. Please confirm the applicable Specifications at the time of placing your order.