



ARGOPRO-600-CC-SEN

Argonaut Pro 600mm Weatherproof Batten, Combine Control, Motion Sensor




PRODUCT INFORMATION	
Product Code	ARGOPRO-600-CC-SEN
MIC	AUB04621070003
Product Description	Argonaut Pro 600mm Weatherproof Batten, Combine Control, Motion Sensor
Mounting Method	Surface Mount/Suspension
Product Construction ¹	Recyclable UV Resistant Polycarbonate (PC) Base with Stainless Steel Clips (SS316)
Diffuser Material	Recyclable UV Resistant Polycarbonate (PC)
UL Flammability Rating	UL94 - V2 Self-extinguishing Polycarbonate (PC)
Halogen Free	Yes
Dimensions L x W x H	655mm x 160mm x 105mm
Weight	1.42kg
Ingress Protection (IP) Rating	IP65
Impact Protection (IK) Rating ²	IK08
Operating Temperature	0°C to 40°C
Supply Voltage	220-240V~ 50Hz
Power Factor	0.91 @ default
Supply Current	84mA +/-20mA
Inrush Current (Max)	17.60A<400µs
Earth Leakage	0.02mA

GENERAL LIGHTING - SPECIFICATION	
Colour Temperature	4000K
Colour Rendering Index (CRI)	≥ 90 (R9 > 50)
LED Colour Consistency	3 SDCM
Short Term Light Modulation (PstLM)	≤ 1.0
Stroboscopic Visibility Measure (SVM)	≤ 0.4
Flicker Free ³	Yes
Luminaire Output Configuration	Fixed Single Output
Total Lumen Output	2564 lm (142.4 lm/W) @ default (refer to next page for details)
Power Consumption	18.0W @ default (refer to next page for details)
Rated LED lifetime ⁴	L70/B50 Ta 40 °C: Reported > 120,000h, Projected 230,800h L80/B20 Ta 40 °C: Reported > 120,000h, Projected 134,600h L90/B10 Ta 40 °C: Reported 63,600h, Projected 63,600h
Driver ⁵	LED Driver - Mustang Pro 50W, SEN
Sensor Capability	Microwave Sensor - High/Low, On/Off, Combine Control




ARGOPRO-600-CC-SEN

Argonaut Pro 600mm Weatherproof Batten, Combine Control, Motion Sensor

PRODUCT INFORMATION - COMPLIANCE	
Green Building Schemes ⁶	Compliant with Green Star Flicker, CRI and MacAdam/SDCM Requirements
Applicable Standards	AS/NZS 3820, AS CISPR 15, AS/NZS 60598.2.1
Compliance Marking (RCM)	

REPLACEMENT PARTS	
Part Number	Description
AUN00000000601	240V Driver
801-00092	240V LED Strip
1190132	Sensor



Power Consumption & Lumen Output	Lamp On	Lamp Min. 10%	Lumen Output
Output (700mA)	18.0W	2.5W	2564 lm

¹ All plastic materials will degrade under UV exposure over time, resulting in potential yellowing and surface degradation. UV stabilised materials are generally suited to indoor or sheltered environments with indirect UV exposure, while UL 746C – F1 rated UV resistant materials are suitable for outdoor applications with direct exposure to UV and moisture, providing enhanced resistance and reducing the rate of UV-induced ageing.

² When luminaire is ceiling mounted using appropriate fixings in accordance with the product instruction.

³ An LED luminaire is considered flicker-free if the SVM value is ≤ 0.4 and PstLM value is ≤ 1.0 .

⁴ The projected value has been calculated by extrapolation of the LM80 data using the Energy Star Calculator.

⁵ Products fitted with the Mustang Pro combo driver have two active (mains-230V) connections. All operating current is supplied via Lem (Permanent Active, unswitched) only and shall be sized accordingly. Lsw (Switched Active, control only) is a mains-voltage control line and carries no load.

⁶ Designed to meet the applicable building scheme requirements at the document version date. For full details, refer to the relevant building scheme specification.

The product details described in this document are current as at the version date of the document. We reserve the right to change product design, specifications or materials (Specifications) as part of our continuous improvement program. Please confirm the applicable Specifications at the time of placing your order.