



ARGOPRO-600-DD

Argonaut Pro, 600mm IP65 Weatherproof Batten, Mains, DALI-2 Driver



PRODUCT INFORMATION	
Part Number	ARGOPRO-600-DD
MIC	UKB00000013001
Description	Argonaut Pro 600mm IP65 Weatherproof Batten, Mains, DALI-2 Driver
Product Construction	Polycarbonate Base & Diffuser w/ Stainless Steel Clips (SS316)
Mounting Method	Surface Mount
Colour Temperature	4000K
Colour Rendering Index (CRI)	>80
Colour Consistency	3 SDCM
Total Lumen Output	2564lm
Power Consumption	17.2W
LED Rated Service Life	L70/B50 Ta 40°C: Reported > 102,000h, Projected 275,000h L80/B20 Ta 40°C: Reported 100,000h, Projected 100,000h L90/B10 Ta 40°C: Reported 43,000h, Projected 43,000h
Sensor Capability	N/A
Ingress Protection (IP)	IP65
Impact Resistant (IK)	IK08
Operating Temperature	0°C to 40°C
Operating Voltage	220-240V~ 50Hz
Power factor	0.91 @ default
Supply Current	82mA +/-20mA
Inrush Current (Peak/Duration)	44.2A<500µs
Earth Leakage	0.18mA
Dimensions L x W x H	655mm x 160mm x 105mm
Weight	1.4kg
Applicable Standards	EN 60598-2-1, BS EN IEC 55015, BS EN 61547, BS EN IEC 61000-3-2
Compliance Marking	

The product details described in this document are current as at the version date of the document. We reserve the right to change product design, specifications or materials (Specifications) as part of our continuous improvement program. Please confirm the applicable Specifications at the time of placing your order.