



ARGOPRO-600-L10-HVG

Argonaut Pro, 600mm IP65 Weatherproof Emergency Batten, L10, Zoneworks HIVE



PRODUCT INFORMATION

Product Code	ARGOPRO-600-L10-HVG
MIC	UKB00000012801
Description	Argonaut Pro, 600mm IP65 Weatherproof Emergency Batten, L10, Zoneworks HIVE
Colour CCT	4000K
Output Configuration	Fixed Single Output
Battery Configuration	Integral Battery
Construction	Polycarbonate Base & Diffuser w/ Stainless Steel Clips (SS316)
Diffuser	Polycarbonate
Mounting	Surface Mount
Operating Mode	Sustained
Testing System	Zonework HIVE (RF) 2.4GHz
Battery	Lithium Nanophosphate (LiFePO4)
Charging Method	Intelligent current limited constant voltage
Sensor Capability	N/A
Dimensions LxWxH (mm)	655mm x 160mm x 105mm
Weight (kg)	1.7kg
Driver / Ballast	LED Driver - 40W, 500-1050mA, 15-50V
Lamp(s)*	LED strip module, 4000K, Ra>80 Lamp(s)* L70/B50 Ta 40°C; LM80 Report >60,000h, Projected 184,000h L80/B20 Ta 40°C; LM80 Report >60,000h, Projected 100,000h L90/B10 Ta 40°C; LM80 Report 43,000h, Projected 43,000h
Supply Voltage	220-240V~ 50Hz
Power Factor	0.85 @ default
Supply Current	108mA +/-20mA
Power Consumption	19W @ default (refer to next page for details)
Inrush Current (Peak/Duration)	43.9A/500µs
Earth Leakage	0.40mA
Total lumen output	2564lm
Emergency lumen output	354lm
Power Consumption	21.6W @ default (refer to next page for details)
Operating Temperature	0°C to 40°C
IP Rating	IP65
Impact Rating	IK08
LED MacAdam Step (SDCM)	3
Luminaire Classification	X 2 ADF 180
Applicable Standards	BS IEC 60598-2-22, BS 5266, BS EN IEC 55015, BS EN 61547, BS EN IEC 61000-3-2
Compliance Marking	



ARGOPRO-600-L10-HVG

Argonaut Pro, 600mm IP65 Weatherproof Emergency Batten, L10,
Zoneworks HIVE

REPLACEMENT PARTS

COMPONENT	PART NUMBER & DESCRIPTION
1533010, 1533230	Battery
1330029	240V Driver
8002754	240V LED Panel
UKM01870560001	Emergency Driver
8003110	Emergency LED Panel
8003330	Node
1533010, 1533230	Battery

Power Consumption & Lumen Output	Max Charge, Lamp On	Standby Charge, Lamp On	Standby Charge, Lamp Off	Lumen Output
Output (700mA)	21.3W	19.0W	0.7W	2564lm

The product details described in this document are current as at the version date of the document. We reserve the right to change product design, specifications or materials (Specifications) as part of our continuous improvement program. Please confirm the applicable Specifications at the time of placing your order.