



ARGOSQ-DD

ARGONAUT SQUARE
WEATHERPROOF LUMINAIRE



PRODUCT INFORMATION	
Part Number	ARGOSQ-DD
MIC	AUS04620440001
Description	Argonaut Square Weatherproof Luminaire with DALI Driver
Output Configuration	Configurable Dual Output
Construction	Die-cast Aluminium Body with Polycarbonate Diffuser
Mounting	Surface mount
Dimensions L x W x H	321mm x 321mm x 97mm
Weight	3.0kg
Diffuser	Polycarbonate
Driver / Ballast	LED Driver-LCA 25W 350-1050mAone4all SC PRE,20-50V
Lamp(s)	LED module, 4000K cool white, Ra>80 L70/B50 Ta 40°C; Reported >60,000hr, Projected 205,000hr L80/B20 Ta 40°C; Reported >60,000hr, Projected 100,000hr L90/B10 Ta 40°C; Reported >43,000hr, Projected 43,000hr
Supply Voltage	220-240V~ 50Hz
Power Factor	0.91
Supply Current	100mA +/- 20mA
Inrush Current (max)	30.8A<100µs
Earth Leakage	0.35mA
Total Lumen Output	3242lm @ 152.9/W @ default (refer to next page for details)
Power Consumption	21.2W @ default (refer to next page for details)
IP Rating	IP65
IK Rating	IK10
Operating Temperature	0°C to 40°C
AS2293 Classification	N/A
Applicable Standards ANZ	AS/NZS3820, AS/NZS2293.3, CISPR15
Compliance Marking (RCM)	

The product details described in this document are current as at the version date of the document. We reserve the right to change product design, specifications or materials (Specifications) as part of our continuous improvement program. Please confirm the applicable Specifications at the time of placing your order.



ARGOSQ-DD
ARGONAUT SQUARE
WEATHERPROOF LUMINAIRE

REPLACEMENT PARTS	
PART NUMBER	DESCRIPTION
8050780	LED Panel
1330038	240V Driver

Power Consumption & Lumen Output	Power Consumption Lamp On	Lumen Output
(470mA) DEFAULT	21.2W	3242lm

The product details described in this document are current as at the version date of the document. We reserve the right to change product design, specifications or materials (Specifications) as part of our continuous improvement program. Please confirm the applicable Specifications at the time of placing your order.