

## **ARGOSQ-LP-HVG** Argonaut Square IP65 Weatherproof Emergency, LP, Zoneworks XT Hive 2.4GHz



PRODUCT INFORMATION					
Part Number	ARGOSQ-LP-HVG				
MIC	AUS02920100001				
Description	Argonaut Square IP65 Weatherproof Emergency, LP, Zoneworks XT Hive 2.4GHz				
Output Configuration	Configurable Dual Output				
Construction	Die-cast Aluminium Body with Polycarbonate Diffuser				
Mounting	Surface mount				
Dimensions L x W x H	321mm x 321mm x 97mm				
Weight	3.5kg				
Operating Mode	Sustained				
Testing System	Zoneworks XT HIVE (RF)				
Battery	Lithium Iron Phosphate, 3.2V 6400mAh				
Charging Method	Intelligent current limited constant voltage				
Diffuser	Polycarbonate				
Driver / Ballast	Clevertronics Stallion 40W				
Lamp(s)	LED module, 4000K cool white, Ra>80 L70/B50 Ta 40ºC; Reported >60,000hr, Projected 205,000hr L80/B20 Ta 40ºC; Reported >60,000hr, Projected 100,000hr L90/B10 Ta 40ºC; Reported >43,000hr, Projected 43,000hr				
Supply Voltage	220-240V~ 50Hz				
Power Factor	0.91				
Supply Current	100mA +/- 20mA				
Inrush Current (max)	30.8A<100µs				
Earth Leakage	0.35mA				
Total Lumen Output	3242lm @ 148lm/W @ default (refer to next page for details)				
Power Consumption	24.2W (MAX Charge - Lamp ON), 21.9W (Standby Lamp ON), 0.7W (Standby Lamp OFF) @ default (refer to next page for details)				
IP Rating	IP65				
IK Rating	IK10				
Operating Temperature	0°C to 40°C				
AS2293 Classification	C <sub>0</sub> =D63 C <sub>90</sub> =D63				
Applicable Standards	AS/NZS3820, CISPR15, AS/NZS2293.3				
Compliance Marking (RCM)					

The product details described in this document are current as at the version date of the document. We reserve the right to change product design, specifications or materials (Specifications) as part of our continuous improvement program. Please confirm the applicable Specifications at the time of placing your order.





**ARGOSQ-LP-HVG** Argonaut Square IP65 Weatherproof Emergency, LP, Zoneworks XT Hive 2.4GHz

REPLACEMENT PARTS			
PART NUMBER	DESCRIPTION		
1550230	BATT:LP 3.2V 6400mAh.200mm lead. BRKT		
8050780	LED:HWSUB: CT10746-D2		
1330094	LED Driver - 40W Stallion, SP2, 470/270mA		
ARGOSQ-LP-CKIT-HVG	EM DRIVER: ARGOSQ, Control Only, LP, OWC, HVG (incl Hive node)		
8003580	PCA: V5 2.4GHz RF Node CT10816-A1 Ext Ant		

The product details described in this document are current as at the version date of the document. We reserve the right to change product design, specifications or materials (Specifications) as part of our continuous improvement program. Please confirm the applicable Specifications at the time of placing your order.

Power Consumption & Lumen Output	Max Charge, Lamp On	Standby Charge, Lamp On	Standby Charge, Lamp Off	Lumen Output
Output 1 (470mA) DEFAULT	24.2W	21.9W	0.7W	3242lm
Output 2 (270mA)	18.7W	16.4W	0.7W	1718lm

