



## ARGOSQ

Argonaut Square IP65 Weatherproof Non-emergency



PRODUCT INFORMATION	
Part Number	ARGOSQ
MIC	UKS00000001401
Description	Argonaut Square IP65 Weatherproof Non-emergency
Output Configuration	Configurable Dual Output
Construction	Die-cast Aluminium Body with Polycarbonate Diffuser
Mounting	Surface Mount
Dimensions L x W x H	321mm x 321mm x 97mm
Weight	3.0kg
Diffuser	Polycarbonate
Driver	Clevertronics Stallion 40W
Lamp(s)	LED Module, 4000K Cool White, Ra>80 L70/B50 Ta 40°C; Reported >60,000hr, Projected 205,000hr L80/B20 Ta 40°C; Reported >60,000hr, Projected 100,000hr L90/B10 Ta 40°C; Reported >43,000hr, Projected 43,000hr
Total Lumen Output	3242lm @ 152.9/W @ Default (Refer to Next Page for Details)
Supply Voltage	220-240V~ 50Hz
Power Factor	0.91
Supply Current	100mA +/- 20mA
Inrush Current (max)	30.8A<100µs
Earth Leakage	0.35mA
Power Consumption	21.2W @ Default (Refer to Next Page for Details)
IP Rating	IP65
IK Rating	IK10
Operating Temperature	-25°C to 40°C
Compliance Marking	
Luminaire Classification	X   2   AD   18 0
Conformity	BS EN IEC 55015, BS EN 61547, BS EN IEC 61000-3-2

Power Consumption & Lumen Output	LAMP ON	LUMEN OUTPUT
Output 2 (470mA) DEFAULT	21.2W	3242lm
Output 1 (270mA)	15.7W	1718lm

REPLACEMENT PARTS	
PART NUMBER	DESCRIPTION
8050780	LED Assembly
1330094	240V Driver

The product details described in this document are current as at the version date of the document. We reserve the right to change product design, specifications or materials (Specifications) as part of our continuous improvement program. Please confirm the applicable Specifications at the time of placing your order