



ARGOWALL-L10-D2

Argonaut Wall Light IP65 Weatherproof, Emergency, L10 Nanophosphate, Maintained, DALI-2 Emergency, Anthracite Grey (RAL7016)



| PRODUCT INFORMATION | |
|--------------------------------|--|
| Part Number | ARGOWALL-L10-D2 |
| MIC | UKS01220070001 |
| Description | Argonaut Wall Light IP65 Weatherproof, Emergency, L10 Nanophosphate, Maintained, DALI-2 Emergency, Anthracite Grey (RAL7016) |
| Construction | Die Cast Aluminium Body with Polycarbonate LED Cover |
| Mounting | Surface Mount (Wall, with LED light source facing downwards) |
| Dimensions L x W x H | 305mm (W) x 310mm (H) x 155mm (D) |
| Weight | 4.6Kg |
| Operating Mode | Maintained (with integrated photocell for automatic on/off operation depending on ambient light levels) |
| Testing System | DALI Registered |
| Battery Type & Manufacturer | Lithium Nanophosphate (LiFePO4), Clevertronics |
| Charging Method | Intelligent Current Limited Constant Voltage |
| Diffuser | Polycarbonate with asymmetric lenses over the LEDs to suit wall mounted, walkway, applications (LED cover fitted with 4 security torx head screws) |
| Lamp(s) | LED module, 4000K, 100,000 Hours, [L70/ B50, Ta 40°C], Ra>80 |
| Operating Voltage | 220-240V AC; 50Hz |
| Total Lumen Output | 360lm (Emergency mode) 1645lm @110lm/W (non-Emergency, mains mode) |
| Power Factor | 0.77 |
| Supply Current | 111mA (Lamps ON Max Charge), 89mA (Lamps ON Standby) |
| Power Consumption | 19.9W (Lamps ON Max Charge), 15.8W (Lamps ON Standby) 1.4W (Lamps OFF Standby) |
| Inrush Current (Peak/Duration) | 6.24A/172µS |
| Earth Leakage | 0.104mA |
| Rated Emergency Duration | 180 minutes |
| IP Rating | IP65 |
| IK Rating | IK10 |
| Operating temperature | 0°C to 30°C |
| Luminaire Classification | X 1 ADF 180 |
| Conformity | BS EN 60598.2.22, BS 5266 |



ARGOWALL-L10-D2

Argonaut Wall Light IP65 Weatherproof, Emergency, L10
Nanophosphate, Maintained, DALI-2 Emergency, Anthracite Grey
(RAL7016)

REPLACEMENT PARTS

| PART NUMBER | DESCRIPTION |
|---------------------|--|
| 1530190 | Battery |
| 1330153 | LED Driver - TCI PRO FLAT 30 BI set to 350mA |
| LCPLED-2.4W-CKIT-D2 | EM DRIVER |

The product details described in this document are current as at the version date of the document. We reserve the right to change product design, specifications or materials (Specifications) as part of our continuous improvement program. Please confirm the applicable Specifications at the time of placing your order