

ARGOWALL-L10-HVG

Argonaut Wall Light IP65 Weatherproof Emergency, Surface Mount, L10 Nanophosphate, Maintained, Zoneworks XT Hive, Anthracite Grey (RAL7016)



Part Number	ARGOWALL-L10-HVG
MIC	UKS01820050002
Description	Argonaut Wall Light IP65 Weatherproof Emergency, Surface Mount, L10 Nanophosphate Maintained, Zoneworks XT Hive, Anthracite Grey (RAL7016)
Construction	Die Cast Aluminium Body with Polycarbonate LED Cover
Mounting	Surface Mount (Wall, with LED light source facing downwards)
Dimensions L x W x H	305mm (W) x 310mm (H) x 155mm (D)
Weight	4.6Kg
Operating Mode	Maintained (with integrated photocell for automatic on/off operation depending on ambient light levels)
Testing System	Zoneworks XT HIVE (RF)
Battery	Lithium Nanophosphate (LiFePO4), Clevertronics
Charging Method	Intelligent Current Limited Constant Voltage
Diffuser	Polycarbonate with asymmetric lenses over the LEDs to suit wall mounted, walkway, applications (LED cover fitted with 4 security torx head screws)
Lamp(s)	LED module, 4000K, 100,000h [L70/ B50, Ta 40°C], Ra>80
Operating Voltage	220-240V AC; 50Hz
Total Lumen Output	360lm (Emergency mode) 1646lm @104lm/W (non-Emergency, mains mode)
Power Factor	0.81
Supply Current	99mA (Lamps ON Max Charge), 87mA (Lamps ON Standby)
Power Consumption	18.4W (Lamps ON Max Charge), 15.8W (Lamps ON Standby) 1.7W (Lamps OFF Standby)
Inrush Current (Peak/Duration)	6.24A / 172 μs
Earth Leakage	0.15mA
Rated Emergency Duration	180 minutes
IP Rating	IP65
IK Rating	IK10
Operating temperature	0°C to 30°C
Compliance Marking	ĽK (€





ARGOWALL-L10-HVG

Argonaut Wall Light IP65 Weatherproof Emergency, Surface Mount, L10 Nanophosphate, Maintained, Zoneworks XT Hive, Anthracite Grey (RAL7016)

PRODUCT INFORMATION	
Luminaire Classification	X 1 ADF 180
Conformity	BS EN 60598.2.22, BS 5266

REPLACEMENT PARTS		
PART NUMBER	DESCRIPTION	
1533190	Battery	
1330153	LED Driver	
8050219	LED Assembly	
UKM00000000101 LCP-WP-2.4W-54V-CKIT-HVGAFOS220	Emergency Driver	
8003645	HIVE Node	

The product details described in this document are current as at the version date of the document. We reserve the right to change product design, specifications or materials (Specifications) as part of our continuous improvement program. Please confirm the applicable Specifications at the time of placing your order

