



ARGOWALL-LP-HVG

Argonaut Wall Light IP65 Weatherproof, Emergency, CLP, Maintained, Zoneworks HIVE, Anthracite Grey (RAL7016)



PRODUCT INFORMATION

Part Number	ARGOWALL-LP-HVG				
MIC	UKS02820190002				
Description	Argonaut Wall Light IP65 Weatherproof, Emergency, CLP, Maintained, Zoneworks HIVE, Anthracite Grey (RAL7016)				
Construction	Die Cast Aluminium Body with Polycarbonate LED Cover				
Mounting	Surface Mount (Wall, with LED light source facing downwards)				
Dimensions L x W x H	305mm (W) x 310mm (H) x 155mm (D)				
Weight	4.6Kg				
Operating Mode	Maintained (with integrated photocell for automatic on/off operation depending on ambient light levels)				
Testing System	Zoneworks XT HIVE (RF) 2.4GHz				
Battery Type & Manufacturer	Lithium Iron Phosphate (LiFePO4), Clevertronics				
Charging Method	Intelligent Current Limited Constant Voltage				
Diffuser	Polycarbonate with asymmetric lenses over the LEDs to suit wall mounted, walkway, applications (LED cover fitted with 4 security torx head screws)				
Lamp(s)	LED module, 4000K, 100,000 Hours, [L70/ B50, Ta 40°C], Ra>80				
Operating Voltage	220-240V AC; 50Hz				
Total Lumen Output	443lm (Emergency mode) 1646lm @104lm/W (non-Emergency, mains mode)				
Power Factor	0.81				
Supply Current	99mA (Lamps ON Max Charge), 87mA (Lamps ON Standby)				
Power Consumption	18.4W (Lamps ON Max Charge), 15.8W (Lamps ON Standby) 1.7W (Lamps OFF Standby)				
Inrush Current (Peak/Duration)	6.24A/172 µs				
Earth Leakage	0.15mA				
Rated Emergency Duration	180 minutes				
IP Rating	IP65				
IK Rating	IK10				
Operating temperature	0°C to 30°C				
Luminaire Classification	X	1	ADF	180	
Conformity	BS EN 60598.2.22, BS 5266				
Compliance Marking	UK CA CE				

REPLACEMENT PARTS

PART NUMBER	DESCRIPTION
1553290	Battery
8050219	LED Panel
1330153	LED Driver
UKM00000000901	Emergency Driver
8003645	Node

*Due to changes in industry standards and Clevertronics policy of product improvement, specification details are subject to change without notice