



ARGOWALLPRO-WW-BLK

Argonaut Wall Light Pro, IP65 Weatherproof, Black (RAL9005)



PRODUCT INFORMATION

Part Number	ARGOWALLPRO-WW-BLK
MIC	UKB00000002601
Description	Argonaut Wall Light Pro, IP65 Weatherproof, Black (RAL9005)
Construction	Die Cast Aluminium Body with Polycarbonate LED Cover
Diffuser	Polycarbonate with asymmetric lenses over the LEDs to suit wall mounted, walkway applications (LED cover fitted with 4 security torx head screws)
Mounting Method	Surface Mount (Wall, with LED light source facing downwards)
Colour Temperature	3000K
Colour Rendering Index (CRI)	>80
Colour Consistency	3 SDCM
Total Lumen Output	1622lm
Power Consumption	14.2W
LED Rated Service Life	L70/B50 > 100,000h at 40°C
Sensor Capability	Photocell for automatic on/off operation depending on ambient light levels
Ingress Protection (IP) Rating	IP65
Impact Resistant (IK) Rating	IK10
Operating Temperature	0°C to 40°C
Operating Voltage	220-240V AC; 50Hz
Power factor	0.90
Supply Current	77mA
Inrush Current (Peak/Duration)	6.96A / 17µs
Earth Leakage	0.05mA
Dimensions L x W x H	310mm x 305mm x 155mm
Weight	4.5kg
Applicable Standards	BS EN IEC 60598-2-1, BS EN IEC 55015, BS EN IEC 61547, BS EN IEC 61000-3-2, BS EN IEC 61000-3-3
Compliance Marking (RCM)	

The product details described in this document are current as at the version date of the document. We reserve the right to change product design, specifications or materials (Specifications) as part of our continuous improvement program. Please confirm the applicable Specifications at the time of placing your order.