



## ARGOWALLPRO-WW-MS-L10-D2-BLK

Argonaut Wall Light Pro ,IP65 Weatherproof ,Emergency ,L10 Nanophosphate ,Maintained , Motion Sensor ,DALI-2 Emergency ,Black (RAL9005)



### PRODUCT INFORMATION

Part Number	ARGOWALLPRO-WW-MS-L10-D2-BLK
MIC	UKB00000002701
Description	Argonaut Wall Light Pro ,IP65 Weatherproof ,Emergency ,L10 Nanophosphate ,Maintained , Motion Sensor ,DALI-2 Emergency ,Black (RAL9005)
Construction	Die Cast Aluminium Body with Polycarbonate LED Cover
Diffuser	Polycarbonate with asymmetric lenses over the LEDs to suit wall mounted, walkway applications (LED cover fitted with 4 security torx head screws)
Mounting Method	Surface Mount (Wall, with LED light source facing downwards)
Colour Temperature	3000K
Colour Rendering Index (CRI)	Ra>80
Colour Consistency	3 SDCM
Total Lumen Output	1622lm
Power Consumption	18.50W (Lamps ON, Max Charge), 15.60W (Lamp on, Standby), 1.9W (Lamp off, Standby)
LED Rated Service Life	L70/B50 > 100,000h at 40°C
Sensor Capability	Microwave Sensor On/Off , photocell for automatic on/off operation depending on ambient light levels
Emergency Operating Mode	Maintained
Emergency Testing System	DALI-2 Emergency
Emergency Lumen Output	363lm
Battery	Lithium Nanophosphate, 6.6V 2500mAh
Luminaire Classification	X   1   ADF   180
Ingress Protection (IP) Rating	IP65
Impact Resistant (IK) Rating	IK10
Operating Temperature	0°C to 40°C
Operating Voltage	220-240V AC; 50Hz
Power factor	0.85 @ default
Supply Current	94mA
Inrush Current (Peak/Duration)	4.30A / 148μs
Earth Leakage	0.15mA
Dimensions L x W x H	310mm x 305mm x 155mm
Weight	4.6kg
Applicable Standards	BS 5266-1, BS EN IEC 60598-2-22, BS EN IEC 55015, BS EN IEC 61547, BS EN IEC 61000-3-2 BS EN IEC 61000-3-3, ETSI EN 301 489-1, ETSI EN 301 489-17
Compliance Marking (RCM)	

The product details described in this document are current as at the version date of the document. We reserve the right to change product design, specifications or materials (Specifications) as part of our continuous improvement program. Please confirm the applicable Specifications at the time of placing your order.