

# **NIFTY LIFELIGHT**



### Simple-to-install LED Recessed Emergency Light

The Nifty encapsulated Lifelight features a new simple-to-install design, producing a D40 Emergency Classification with low power consumption.

Utilising long-lasting Lithium Iron Phosphate battery technology, the Nifty recessed version is supplied with a 140mm adapter plate for retrofit applications and is IC-4 rated for safe installation alongside insulation.

### Applications



Schools

Office Buildings



) Apartments

Retail outlets

### **Features and Benefits**

- AS/NZS 2293.3 compliant
- D40 emergency classification
- Hassle free encapsulated unit
- 140mm adaptor plate for retrofitting
- Low power consumption
- Lithium Iron Phosphate battery
- IC-4 rated for safe recessed installation alongside insulation











## **NIFTY LIFELIGHT**

Tis the 100

Seaso :0

be jo

ORDERING INFORMATION	TS									
Standard - White	NIFTY									
Carton Quantity	20 Pieces									
Weight - Single (Carton)	0.4kg (8.3kg)									
Dimensions (Diameter x Height)	110mm x 54mm									
Dimensions - Adaptor Plate (Diameter)	140mm									
Dimensions - Ceiling Hole Cut-Out	90mm									
Dimensions - Minimum Ceiling Depth	45mm									
POWER, LAMPS AND BATTERY	TS									
Power Consumption (Standby / Max)	0.5W / 1.6W									
Lamp(s)	4 x LED									
Battery	Lithium Iron Phosphate									
Voltage (V) / Capacity (mAh)	3.2V / 1500mAh									
Charging Method	Intelligent Current Limited Constant Voltage									
TECHNICAL SPECIFICATIONS		CLASSIFICATION	TS							
Operating Mode	Non-Maintained	со	D40							
Voltage (V) Frequency (Hz)	220-240V (50Hz)	C90	D40							

1

1

:first5

SPACING TABLE AND MOUNTING HEIGHTS – AS/NZS 2293.1:2018 (MINIMUM LIGHT LEVEL OF 0.2 LUX)														
Classification	2.1m	2.4m	2.7m	3.0m	3.3m	3.6m	4.0m	4.5m	5.0m	6.0m	7.0m	8.0m	9.0m	10.0m
D40	11.5	13.2	14.8	16.5	18.1	19.5	20.1	20.7	21.2	22.1	22.6	23.0	23.1	23.0

1°C to 40°C


IP40

#### For 1 lux and AS/NZS 2293.1:2005 spacing tables please visit: https://clevertronics.com.au/spacing-tables/

Operating Temperature

Ingress Protection Rating (IP)

\*Warranty information located at: https://clevertronics.com.au/warranty-statement/



Dimensions (mm)

#### clevertronics.com.au



1 Caribbean Drive, Scoresby VIC 3179 P +61 3 9559 2700 F +61 3 9559 2799 E info@clevertronics.com.au

Clevertronics is committed to continuously improving its products. All features and specifications are subject to change without prior notice. \_PRODUCT SHEETS – AU Nifty Lifelight 04JUL23