



## CLEVERTRONICS LP LED WEATHERPROOF BUNKALITE, BLACK



### PRODUCT INFORMATION

Catalogue Number	CBKLEDN-DALI-BLK
Description	LP Premium Bunkalite IP65 Weatherproof Non-Maintained Emergency Luminaire, Black
Construction	Base Material: Die-cast aluminium Diffuser Cover Material: Opal Polycarbonate
Mounting	Surface Mount
Dimensions L x W x H	Diameter 360mm, Depth 145mm
Weight	4.5kg
Operating Mode	Non-maintained
Testing System	DALI compatible
Battery	Lithium Iron Phosphate, 3.2V 3200mAh
Charging Method	Intelligent Current Limited Constant Voltage
Diffuser	Polycarbonate
Lamp(s)	LED module, 4,000K natural white, 50,000h life, Ra>80
Operating Voltage	240V AC; 50Hz
Power Consumption	1.0 Watts (Standby)
IP Rating	IP65
Operating Temperature	0°C to 40°C
AS2293 Classification	C <sub>0</sub> =D25 C <sub>90</sub> =D25
Impact Rating	IK10

### REPLACEMENT PARTS

PART NUMBER	DESCRIPTION
1550010	BATT:LP 3.2V 3200mAh 200mm lead,BRKT.
CLIFE-CKIT-NP	Lifelight, Control Only, LP, No Plug
8002200	PCA:DALI Node, #CT10410-A3

**DALI EM****LP** LITHIUM IRON  
PHOSPHATE  
PREMIUM  
PROVEN PROJECT PERFORMANCE