



CBKLEDN-HV-BLK

Bunkalite, Weatherproof Circular Emergency, LP, Non-Maintained,
Zoneworks XT Hive, Black



PRODUCT INFORMATION

Part Number	CBKLEDN-HV-BLK
MIC	AUS02820230002
Description	Bunkalite, Weatherproof Circular Emergency, LP, Non-Maintained, Zoneworks XT Hive, Black
Construction	Base Material: Die-cast Aluminium Diffuser Cover Material: Opal Polycarbonate
Mounting	Surface Mount
Dimensions L x W x H	Diameter 360mm, Depth 145mm
Weight	4.5kg
Operating Mode	Non-Maintained
Testing System	Zoneworks XT HIVE (RF)
Battery	Lithium Iron Phosphate, 3.2V 3200mAh
Charging Method	Intelligent Current Limited Constant Voltage
Diffuser	Polycarbonate
Driver / Ballast	Constant current, 500mA, 50,000hrs
Lamp(s)	LED module
Operating Voltage	240V AC; 50Hz
Power Consumption	4.5W (Max), 1.3W (Standby)
Inrush Current (Max)	0.24A, 2.4µs
Earth Leakage	N/A
IP Rating	IP65
IK Rating	IK10
Operating Temperature	0°C to 40°C
AS2293 Classification	C0=D50, C90=D50
Applicable Standards	AS/NZS3820, CISPR15, AS/NZS2293.3
Compliance Marking (RCM)	

REPLACEMENT PARTS

PART NUMBER	DESCRIPTION
1550010	Battery
8011800	LED Strip
AUM02870580001 CLIFE-CKIT-HVEXTA-NP-220	Driver
8003194	HV Node

The product details described in this document are current as at the version date of the document. We reserve the right to change product design, specifications or materials (Specifications) as part of our continuous improvement program. Please confirm the applicable Specifications at the time of placing your order