



CBKLEDS-D2-BLK

Bunkalite IP65 Weatherproof Circular Emergency, CLP, Sustained, DALI-2 Emergency, Black



PRODUCT INFORMATION

Part Number	CBKLEDS-D2-BLK				
MIC	UKS02220160001				
Description	Bunkalite IP65 Weatherproof Circular Emergency, CLP, Sustained, DALI-2 Emergency, Black				
Construction	Base Material: Die-cast aluminium Diffuser Cover Material: Opal Polycarbonate				
Mounting	Surface Mount				
Dimensions L x W x H	360mm (Diameter), 145mm (Height)				
Ceiling Cut-Out	N/A				
Minimum Ceiling Depth	N/A				
Weight	4.5kg				
Operating Mode	Sustained (Combined Non-Maintained)				
Testing System	DALI-2				
Battery Type & Manufacturer	Lithium Iron Phosphate, Clevertronics				
Charging Method	Intelligent current limited constant voltage				
Lamp(s)	LED module, 4,000K natural white, 50,000h life (L70/B50), Ra>80				
Operating Voltage	220-240V AC; 50Hz				
Supply Current	0.071A				
Power Factor	0.93				
Total lumen output	260lm (Emergency) 1435lm (240V/Maintained Mode)				
Power Consumption	1.2 Watts (Standby), 21 Watts (Max)				
Inrush Current (Peak/Duration)	10.2A				
Earth Leakage	0.145mA				
IP Rating	IP65				
Impact Rating	IK10				
Operating temperature	0°C to 40°C				
Maximum Case Temperature	N/A				
Rated Emergency Duration	180 minutes				
Luminaire Classification	X	2	ADF	180	
Compliance Marking	UK CA CE				
Appliance Class	Class 1				
Applicable Standards	BS EN 60598-2-22, BS 5266				



CBKLEDS-D2-BLK

Bunkalite IP65 Weatherproof Circular Emergency, CLP, Sustained, DALI-2 Emergency, Black

REPLACEMENT PARTS

PART NUMBER	DESCRIPTION
1553230	Battery
1331101-B	240V Driver
UKM02270160002	Emergency Driver
8011801	LED Strip
8003062	Node

*Due to changes in industry standards and Clevertronics policy of product improvement, specification details are subject to change without notice.