



CBKLEDS-DD-BLK

Bunkalite IP65 Weatherproof Circular Emergency, LP, Sustained, DALI Driver, Clevertest Plus, Black



PRODUCT INFORMATION

Part Number	CBKLEDS-DD-BLK
MIC	AUS02320150002
Description	Bunkalite IP65 Weatherproof Circular Emergency, LP, Sustained, DALI Driver, Black, Clevertest Plus
Construction	Base Material: Die-cast Aluminium Diffuser Cover Material: Opal Polycarbonate
Mounting	Surface Mount
Dimensions	Diameter 360mm, Depth 145mm
Weight	4.5kg
Operating Mode	Sustained
Testing System	Clevertest Plus Enabled (Not activated by default)
Battery	Lithium Iron Phosphate, 3.2V 3200mAh
Charging Method	Intelligent Current Limited Constant Voltage
Diffuser	Polycarbonate
Driver	Constant current, 480mA, 50,000hrs
Lamp(s)	LED module, 4,000K natural white, 50,000h life, Ra>80
Operating Voltage	240V AC; 50Hz
Power Factor	0.9
Total Lumen Output	1900lm @ 127.5lm/W (based on non-emergency version)
Power Consumption	18.1 Watts (MAX Lamps ON), 1 Watts (Standby Lamp OFF)
Inrush Current (Max)	10.2A @106µs
Earth Leakage	0A
IP Rating	IP65
IK Rating	IK10
Operating Temperature	0°C to 40°C
AS2293 Classification	C0=D50 C90=D50
Applicable Standards	AS/NZS3820, CISPR15, AS/NZS2293.3
Compliance Marking (RCM)	

REPLACEMENT PARTS

PART NUMBER	DESCRIPTION
1550010	Battery
AUM02370470001 CLIFE-CKIT-NP-220	Driver
1330160	240 Driver
8011800	LED

The product details described in this document are current as at the version date of the document. We reserve the right to change product design, specifications or materials (Specifications) as part of our continuous improvement program. Please confirm the applicable Specifications at the time of placing your order