



CBKLEDS-DD-D2-WHT

CLEVERTRONICS LP LED Weatherproof Bunkalite White



PRODUCT INFORMATION

Part Number	CBKLEDS-DD-D2-WHT
MIC	AUS02220370001
Description	LP Premium Bunkalite IP65 Weatherproof Emergency Luminaire with Dali Driver, White
Construction	Base Material: Die-cast aluminium Diffuser Cover Material: Opal Polycarbonate
Mounting	Surface Mount
Dimensions L x W x H	Diameter 360mm, Depth 145mm
Weight	4.5kg
Operating Mode	Sustained
Testing System	DALI 2
Battery	Lithium Iron Phosphate, 3.2V 3200mAh
Charging Method	Intelligent Current Limited Constant Voltage
Diffuser	Polycarbonate
Driver	Constant current, 500mA, 50,000hrs
Lamp(s)	LED module, 4,000K natural white, 50,000h life, Ra>80
Operating Voltage	240V AC; 50Hz
Power Factor	0.9
Power Consumption	1.3W (Standby) 21W (Max)
Total Lumen	1945lm @ 120.8lm/W
Inrush Current (Max)	
Earth Leakage	0.142mA
IP Rating	IP65
Operating Temperature	0°C to 40°C
AS2293 Classification	C0=D25, C90=D25
Applicable Standards	AS/NZS3820, CISPR15, AS/NZS2293.3
Compliance Marking (RCM)	

REPLACEMENT PARTS

PART NUMBER	DESCRIPTION
1550010	Battery
8002801	Combined EM and 240V LED
AUM02270550001 CLIFE-CKIT-D2-NP	Driver
1330045	240V Driver
8003062	DALI 2 Node

The product details described in this document are current as at the version date of the document. We reserve the right to change product design, specifications or materials (Specifications) as part of our continuous improvement program. Please confirm the applicable Specifications at the time of placing your order.