

**CLEVERTRONICS LP LED WEATHERPROOF BUNKALITE, WHITE****PRODUCT INFORMATION**

Catalogue Number	CBKLEDS-DD-DALI-WHT
Description	LP Premium Bunkalite IP65 Weatherproof Emergency Luminaire with Dali Driver, White
Construction	Base Material: Die-cast aluminium Diffuser Cover Material: Opal Polycarbonate
Mounting	Surface Mount
Dimensions L x W x H	Diameter 360mm, Depth 145mm
Weight	4.5kg
Operating Mode	Sustained
Testing System	DALI compatible
Battery	Lithium Iron Phosphate, 3.2V 3200mAh
Charging Method	Intelligent Current Limited Constant Voltage
Diffuser	Polycarbonate
Driver	Constant current, 500mA, 50,000hrs
Lamp(s)	LED module, 4,000K natural white, 50,000h life, Ra>80
Operating Voltage	240V AC; 50Hz
Power Factor	0.9
Total lumen output	1400 lm @ 87lm/W (Based on non-emergency version)
Power Consumption	17 Watts (Lamps ON), 1.0 Watts (Lamp OFF)
IP Rating	IP65
Operating Temperature	0°C to 40°C
AS2293 Classification	C ₀ =D25 C ₉₀ =D25
Impact Rating	IK10

REPLACEMENT PARTS

PART NUMBER	DESCRIPTION
1550010	BATT:LP 3.2V 3200mAh 200mm lead,BRKT.
CLIFE-CKIT-NP	Lifelight, Control Only, LP, No Plug
1330045	LED Driver - 17w 250-700mA, Dimm
8002200	PCA:DALI Node, #CT10410-A3

DALI EM**LP** LITHIUM IRON PHOSPHATE

PREMIUM

PROVEN PROJECT PERFORMANCE