



CBKLEDS-DD-HVG-BLK

CLEVERTRONICS CLP LED WEATHERPROOF BUNKALITE
WITH DALI DRIVER – WHITE (ZONWORKS HIVE)



PRODUCT INFORMATION				
Part Number	CBKLEDS-DD-HVG-BLK			
MIC	UKS02820180001			
Description	CLP Premium Bunkalite IP65 Weatherproof Emergency Luminaire with Dali Driver, Black body			
Construction	Base Material: Die-cast aluminium Diffuser Cover Material: Opal Polycarbonate			
Mounting	Surface Mount			
Dimensions L x W x H	360mm (Diameter), 145mm (Height)			
Weight	4.5kg			
Operating Mode	Sustained (Combined Non-Maintained)			
Testing System	Zoneworks XT HIVE (RF)			
Battery Type & Manufacturer	Lithium Iron Phosphate (LiFePO4), Clevertronics			
Charging Method	Intelligent Current Limited Constant Voltage			
Driver	Constant current, 500mA, 50,000hrs			
Lamp(s)	LED module, 4,000K natural white, 50,000h life (L70/B50), Ra>80			
Operating Voltage	240V AC; 50Hz			
Total Lumen Output	1945lm @ 121lm (Based on non-emergency version)			
Power Consumption	21 Watts (Max lamps on), 1.3 Watts (Standby lamps off)			
Rated Emergency Duration	180 minutes			
IP Rating	IP65			
IK Rating	IK10			
Operating temperature	0°C to 40°C			
Protection	<ul style="list-style-type: none">• Battery overvoltage & overcurrent protection• Battery deep discharge protection• Supply voltage polarity reversal protection• Battery short-circuit protection (charging will resume upon removal of fault)• Kit box (enclosure) of lamp controlgear provides protection against accidental contacts with live parts			
Luminaire Classification	X	2	ADF	180
Conformity	BS EN 60598-2-22, BS 5266			

*Due to changes in industry standards and Clevertronics policy of product improvement, specification details are subject to change without notice



CBKLEDS-DD-HVG-BLK
CLEVERTRONICS CLP LED WEATHERPROOF BUNKALITE
WITH DALI DRIVER – WHITE (ZONWORKS HIVE)

REPLACEMENT PARTS

PART NUMBER	DESCRIPTION
1550230	Battery
UKM02870060001 CLIFE-CKIT-HVG-IC1-650	Driver Pack
1330045	LED Driver - 17w 250-700mA, Dimm
80011801	LED strip
8003340	RF Node

*Due to changes in industry standards and Clevertronics policy of product improvement, specification details are subject to change without notice