

CBKLEDS-WHTCLEVERTRONICS CLP LED WEATHERPROOF BUNKALITE



PRODUCT INFORMATION			
Part Number	CBKLEDS-WHT		
MIC	UKS02320060001		
Description	CLP Premium Bunkalite IP65 Weatherproof Emergency Luminaire, with Clevertest Plus Enabled		
Construction	Base Material: Die-cast aluminium Diffuser Cover Material: Opal Polycarbonate		
Mounting	Surface Mount		
Dimensions L x W x H	360mm (Diamater), 145mm (Height)		
Operating Mode	Sustained (Combined Non-Maintained)		
Testing System	Clevertest Plus Enabled (Not activated by default)		
Battery Type & Manufacturer	Lithium Iron Phosphate, Clevertronics		
Charging Method	Intelligent current limited constant voltage		
Driver	Constant current, 500mA, 50,000hrs		
Lamp(s)	LED module, 4,000K natural white, 50,000h life (L70/B50), Ra>80		
Weight	4.5kg		
Operating Voltage	220-240V AC; 50Hz		
Total lumen output	1945lm @ 121lm (Based on non-emergency version)		
Power Consumption	1.2 Watts (Standby), 21.0 Watts (Max)		

^{*}Due to changes in industry standards and Clevertronics policy of product improvement, specification details are subject to change without notice.





CBKLEDS-WHT CLEVERTRONICS CLP LED WEATHERPROOF BUNKALITE

PRODUCT INFORMATION						
Rated Emergency Duration	180 minutes					
IP Rating	IP65					
IK Rating	IK10					
Operating temperature	0°C to 40°C					
Protection	 Battery overvoltage & overcurrent protection Battery deep discharge protection Supply voltage polarity reversal protection Battery short-circuit protection (charging will resume upon removal of fault) Kit box (enclosure) of lamp control gear provides protection against accidental contacts with live parts 					
Luminaire Classification	Х	2	AD	180		
Applicable Standards	BS EN 60598-2-22, BS 5266					
Compliance Marking	UK C €					

REPLACEMENT PARTS			
PART NUMBER	DESCRIPTION		
1550230	BATT:LP 3.2V 6400mAh.200mm lead. BRKT		
1330049	LED Driver - LC 20w 350/500/700mA flexC SR ADV		
UKM02370110001 CLIFE-CKIT-IC1-650	Lifelight, Control Only,CLP, CTP, 650mA,OWC,NoPlug		
8011800	SUBASSY: HT10585-A2 CCIRC LED 9S8P 2835 4000K		

^{*}Due to changes in industry standards and Clevertronics policy of product improvement, specification details are subject to change without notice.

