

CBKLEDS-WW-BLK

Bunkalite IP65 Weatherproof Circular Emergency, LP, Sustained, Clevertest Plus, Black



Part Number	CBKLEDS-WW-BLK
MIC	AUS02320210002
Description	Bunkalite IP65 Weatherproof Circular Emergency, LP, Sustained, Clevertest Plus Black
Construction	Base Material: Die-cast Aluminium Diffuser Cover Material: Opal Polycarbonate
Mounting	Surface Mounted
Dimensions	Diameter 360mm, Depth 145mm
Weight	4.5kg
Operating Mode	Sustained. Minimum to maximum light control via the microwave sensor. Low level comfort light when no presence detected ramping to maximum When presence detected.
Testing System	Clevertest Plus Enabled (not activated by default)
Battery	Lithium Iron Phosphate, 3.2V 3200mAh
Charging Method	Intelligent Current Limited Constant Voltage
Diffuser	Polycarbonate
Lamp(s)	LED module, 3,000K warm white, 50,000h life, Ra>80
Operating Voltage	240V AC; 50Hz
Power Factor	0.9
Total Lumen Output	1976lm @ 132.5lm/W (based on non-emergency version)
Power Consumption	1 W/3.4W/17.9W (STBY/PWR-ON/MAX)
Inrush Current (Peak/Duration)	24.3A/45.6µs
Earth Leakage	0.254mA
IP Rating	IP65
IK Rating	IK10
Operating Temperature	0°C to 40°C
AS2293 Classification	C0=D50 C90=D50
Applicable Standards	AS/NZS3820, CISPR15, AS/NZS2293.3
Compliance Marking (RCM)	&

REPLACEMENT PARTS	
PART NUMBER	DESCRIPTION
1550010	Battery
801-00048	LED Panel
1331102-B	240V Driver
AUM02370470001	Emergency Driver

The product details described in this document are current as at the version date of the document. We reserve the right to change product design, specifications or materials (Specifications) as part of our continuous improvement program. Please confirm the applicable Specifications at the time of placing your order.

