

CBKLEDS-WW-DD-GRY

Bunkalite IP65 Weatherproof Circular Emergency, LP, Sustained, DALI Driver, Clevertest Plus, Warm White LED, Grey



PRODUCT INFORMATION	
Part Number	CBKLEDS-WW-DD-GRY
MIC	AUS02320340001
Description	Bunkalite IP65 Weatherproof Circular Emergency, LP, Sustained, DALI Driver, Clevertest Plus, Warm White LED, Grey
Construction	Base Material: Die-cast Aluminium Diffuser Cover Material: Opal Polycarbonate
Mounting	Surface Mount
Dimensions	Diameter 360mm, Depth 145mm
Weight	4.5kg
Operating Mode	Sustained
Testing System	Clevertest Plus Enabled
Battery	Lithium Iron Phosphate, 3.2V 3200mAh
Charging Method	Intelligent Current Limited Constant Voltage
Diffuser	Polycarbonate
LED Driver	Tridonic LCA 17W 250-700mA one4all SC PRE (DALI)
Lamp(s)	LED module, 3,000K Warm White, 50,000h Life, Ra>80
Operating Voltage	220-240V AC; 50Hz
Power Factor	0.9
Total Lumen Output	1851lm @ (115lm/W Non-emergency Version)
Power Consumption	1.3W (Standby), 21W (Max)
IP Rating	IP65
Impact Rating	IK10
Operating Temperature	0°C to 40°C
AS2293 Classification	C0=D32 C90=D32 (Ceiling Mount), C0=D5 C90=D5 (Wall Mount)
Applicable Standards	AS/NZS3820, CISPR15, AS/NZS2293.3
Compliance Marking (RCM)	&

REPLACEMENT PARTS	
PART NUMBER	DESCRIPTION
1550010	Battery
8002802	LED Panel
1330045	240V Driver
AUM02870100001 CLIFE-CKIT-HVEXTA-NP	Emergency Driver

The product details described in this document are current as at the version date of the document. We reserve the right to change product design, specifications, or materials (Specifications) as part of our continuous improvement program. Please confirm the applicable Specifications at the time of placing your order

