



CBKLEDS-WW-WHT

CLEVERTRONICS LP LED WEATHERPROOF BUNKALITE
WITH WARM WHITE LED – WHITE BODY



PRODUCT INFORMATION

Part Number	CBKLEDS-WW-WHT
MIC	AUS02320230001
Description	LP Premium Bunkalite IP65 Weatherproof Emergency Luminaire, White Body, Warm White LED, Enabled with Clevertest Plus
Construction	Base Material: Die-cast Aluminium Diffuser Cover Material: Opal Polycarbonate
Mounting	Surface Mounted
Dimensions L x W x H	Diameter 360mm, Depth 145mm
Weight	4.5 kg
Operating Mode	Sustained
Testing System	Clevertest Plus Enabled (Not activated by default)
Battery	Lithium Iron Phosphate, 3.2V 3200mAh
Charging Method	Intelligent Current Limited Constant Voltage
Diffuser	Polycarbonate
Driver	LC 20W (500mA)
Lamp(s)	LED module, 3,000K warm white, 50,000h life, Ra>80
Operating Voltage	240V AC; 50Hz
Power Factor	0.9
Total lumen output	1851lm @ 115lm/W (based on non-emergency version)
Power Consumption	21W (MAX Charge-Lamp ON), 17W (Standby-Lamp ON), 1W (Standby-Lamp OFF)
IP Rating	IP65
Operating Temperature	0°C to 40°C
Impact Rating	IK10
AS2293 Classification	C0=D32 C90=D32
Applicable Standards	AS/NZS3820, CISPR15, AS/NZS2293.3
Compliance Marking (RCM)	

REPLACEMENT PARTS

PART NUMBER	DESCRIPTION
1550010	BATT:LP 3.2V 3200mAh 200mm lead,BRKT.
8002802	PCA: CLE 220mm 2500lm 830 ADV4 EM SO
1330049	LED Driver - LC 20w 350/500/700mA flexC SR ADV
AUM02370170001 CLIFE-CKIT-NP	Lifelight, Control Only, LP, CTP, OWC, No Plug

The product details described in this document are current as at the version date of the document. We reserve the right to change product design, specifications or materials (Specifications) as part of our continuous improvement program. Please confirm the applicable Specifications at the time of placing your order.