

CBS2L2S-LT-WG-HV

Odyssey Wireguard 600mm Emergency Batten, LP, Zoneworks XT Hive



PRODUCT INFORMATION	
Part Number	CBS2L2S-LT-WG-HV
MIC	AUB02810240001
Description	Odyssey Wireguard 600mm Emergency Batten, LP, Zoneworks XT Hive
Construction	Powder coated steel body with PC/ABS end caps
Mounting	Surface mount
Dimensions L x W x H	664mm x 120mm x 108mm
Weight	2.2kg
Operating Mode	Sustained
Testing System	Zoneworks XT Hive (RF)
Battery	Lithium Iron Phosphate, 3.2V 3000mAh
Charging Method	Intelligent current limited constant voltage
Diffuser	Wire guard
Lamp(s)	2 x Ozon LED Tube T8, 8W/840, 30,000hours
Operating Voltage	240V AC; 50Hz
Power Consumption	1.3W/20.5W (STDBY/MAX)
Inrush Current (Max)	твс
Earth Leakage	0.011mA
Total Lumen Output	1760lm @110lm/W (based on the non-emergency version)
Operating Temperature	1°C to 40°C
IP Rating	IP20
AS2293 Classification	C0=D40 C90=D40
Applicable Standards	AS/NZS3820, CISPR15, AS/NZS2293.3
Compliance Marking (RCM)	

REPLACEMENT PARTS	
PART NUMBER	DESCRIPTION
1550050	Battery
3170082	LED Tube
8050215	Emergency LED
AUM02870160001 CLIFE-CKIT-HV-NP	Driver Pack
8003194	HIVE Node

The product details described in this document are current as at the version date of the document. We reserve the right to change product design, specifications or materials (Specifications) as part of our continuous improvement program. Please confirm the applicable Specifications at the time of placing your order.

