



CBS2L2S-LT-WG

Odyssey Wireguard 600mm Emergency Batten, LP, Clevertest Plus



PRODUCT INFORMATION

Part Number	CBS2L2S-LT-WG
MIC	AUB02310050002
Description	Odyssey Wireguard 600mm Emergency Batten, LP, Clevertest Plus
Construction	Powder coated steel body with PC/ABS end caps
Mounting	Surface mount
Dimensions L x W x H	664mm x 120mm x 108mm
Weight	2.2kg
Operating Mode	Sustained
Testing System	Clevertest Plus Enabled (Not activated by default)
Battery	Lithium Iron Phosphate 3.2V 3200mAH
Charging Method	Intelligent Current Limited Constant Voltage
Diffuser	Wire Guard
Driver / Ballast	Integrated in LED Tubes
Lamp(s)	2 x Ozon LED Tube T8, 8W/840, 30,000hours
Operating Voltage	240V AC; 50Hz
Power Factor	0.95
Power Consumption	1.0W/20.2W (STDBY/MAX)
Inrush Current (Max)	TBC
Earth Leakage	0.011mA
Total Lumen Output	1760lm @110lm/W
Operating Temperature	1°C to 40°C
IP Rating	IP20
Impact Rating	N/A
AS2293 Classification	C0=40, C90=40
Applicable Standards	AS/NZS3820, CISPR15, AS/NZS2293.3
Compliance Marking (RCM)	

REPLACEMENT PARTS

PART NUMBER	DESCRIPTION
1550050	Battery
3170082	LED TUBE x 2
AUM02370170001 CLIFE-CKIT-NP	Emergency Driver

The product details described in this document are current as at the version date of the document. We reserve the right to change product design, specifications or materials (Specifications) as part of our continuous improvement program. Please confirm the applicable Specifications at the time of placing your order.