

CLEVERTRONICS LP 600MM ODYSSEY QUANTUM LED DIFFUSED BATTEN (DALI)



PRODUCT INFORMATION

Catalogue Number	CBS2LEDS-DIF-DALI
MIC	AUB02211090002
Description	LP Premium Odyssey Quantum LED 600mm Diffused Batten with LED Emergency Pod
Construction	Powder coated steel body with acrylic prismatic diffuser and PC/ABS end caps
Mounting	Surface Mount
Dimensions L x W x H	664mm x 120mm x 108mm
Weight	2.0kg
Operating Mode	Sustained
Testing System	DALI Registered
Battery	Lithium Iron Phosphate 3.2V 3200mAh
Charging Method	Intelligent Current Limited Constant Voltage
Diffuser	Prismatic
Driver	LED Driver - 40W, 500-1050mA, 15-50V
Lamp(s)	LED strip module, 4,000K natural white, 50,000h life [L70/B50 Ta 40°C], Ra>80
Operating Voltage	240V AC; 50Hz
Power Factor	0.95
Total lumen output	2187lm @ 105lm /W
Power Consumption	25W (Max charging, Lamp ON), 22W (Standby, Lamp ON), 1W (Standby, Lamp OFF)
IP Rating	IP20
Operating Temperature	1°C to 40°C
AS2293 Classification	C ₀ =D40 C ₉₀ =D40

REPLACEMENT PARTS

PART NUMBER	DESCRIPTION
1550050	Battery, LP 3.2V 3200mAh 70mm lead, no Bracket
8002695	PCA:LED Strip 8S6P, ALS-13-840-0-02-B
1330029	LED Driver - 40W, 500-1050mA, 15-50V
AUM02270170002 CLIFE-CKIT-DALI-NP	Lifelight, Control Only, Dali Reg, LP, No Plug (incl. DALI Node)
8003060	PCA: New DALI #CT10629-Ax

The product details described in this document are current as at the version date of the document. We reserve the right to change product design, specifications or materials (Specifications) as part of our continuous improvement program. Please confirm the applicable Specifications at the time of placing your order