



CBS2LEDS-DIF-HV

CLEVERTRONICS LP ODYSSEY QUANTUM 600MM
LED DIFFUSED BATTEN (ZONWORKS XT HIVE)



PRODUCT INFORMATION

Part Number	CBS2LEDS-DIF-HV
MIC	AUB02810020002
Description	LP Premium Quantum 600mm LED Diffused Batten with LED Emergency Pod
Construction	Powder Coated Steel Body with Acrylic Prismatic Diffuser and PC/ABS End Caps
Mounting	Surface Mount
Dimensions L x W x H	664mm x 120mm x 108mm
Weight	2.0 kg
Operating Mode	Sustained
Testing System	Zoneworks XT HIVE (RF)
Battery	Lithium Iron Phosphate 3.2V 3200mAh
Charging Method	Intelligent Current Limited Constant Voltage
Diffuser	Acrylic Prismatic
Driver / Ballast	Osram 40W, 500-1050mA, 15-50V (700mA)
Lamp(s)	LED Strip Module, 4,000K Natural White, 50,000h Life [L70/B50 Ta 40°C], Ra>80
Operating Voltage	240V AC; 50Hz
Power Factor	0.95
Power Consumption	25W (MAX Charge - Lamp ON), 20W (Standby Lamp ON), 1.2W (Standby Lamp OFF)
Total Lumen Output	2187lm @ 105lm/W
Operating Temperature	1°C to 40°C
IP Rating	IP20
AS2293 Classification	C ₀ =D40 C ₉₀ =D40
Applicable Standards	AS/NZS3820, CISPR15, AS/NZS2293.3
Compliance Marking (RCM)	

REPLACEMENT PARTS

PART NUMBER	DESCRIPTION
1550050	Battery, LP 3.2V 3200mAh 70mm lead, no Bracket
8002695	PCA:LED Strip 8S6P, ALS-13-840-0-02-B
1330029	LED XZ Driver – 40W, 500-1050mA, 15-50V, 700mA
AUM02870100001 CLIFE-CKIT-HVEXTA-NP	Lifelight, Control Only, HV, LP, No Plug (incl. Hive node)

The product details described in this document are current as at the version date of the document. We reserve the right to change product design, specifications or materials (Specifications) as part of our continuous improvement program. Please confirm the applicable Specifications at the time of placing your order.