

CBS2N-HVG

Bare Emergency Batten 600mm, Lifelight, Surface Mount, LP, Zoneworks XT Hive 2.4GHz



PRODUCT INFORMATION	
Part Number	CBS2N-HVG
MIC	AUB02910110001
Description	Bare Emergency Batten 600mm, Lifelight, Surface Mount, LP, Zoneworks XT Hive 2.4GHz
Construction	Powder coated Steel Body and ABS/Polycarbonate End Caps
Mounting	Surface Mount
Dimensions L x W x H	610mm x 110mm x 50mm
Operating Mode	Non-maintained
Testing System	Zoneworks XT HIVE (RF)
Battery	Lithium Iron Phosphate, 3.2V 3200mAh
Charging Method	Intelligent Current Limited Constant Voltage
Lamp(s)	Single white LED (Lifetime warranty on the lamp head and loom assembly)
Operating Voltage	240V AC; 50Hz
Power Consumption	1.0 Watts (Standby), 4.5Watts (Max)
IP Rating	IP20
Operating Temperature	1°C to 40°C
AS2293 Classification	C ₀ =D40 C ₉₀ =D40
Applicable Standards	AS/NZS3820, CISPR15, AS/NZS2293.3
Compliance Marking (RCM)	<u>&</u>

REPLACEMENT PARTS	
PART NUMBER	DESCRIPTION
1550010	BATT:LP 3.2V 3200mAh 200mm lead,BRKT.
1100925	LifeLight Head Assembly, Round, LT, 1LED
CLIFE-CKIT-HVGEXTA-NP	Lifelight, Control Only, HVG, LP, No Plug (incl. Hive node)
8003580	PCA: V5 2.4GHz RF Node CT10816-A1 Ext Ant

The product details described in this document are current as at the version date of the document. We reserve the right to change product design, specifications or materials (Specifications) as part of our continuous improvement program. Please confirm the applicable Specifications at the time of placing your order.

