



CBS4LEDS-DIF-MS-HL-HV

Odyssey Diffused 1200mm Emergency Batten, LP, Motion Sensor, Zoneworks XT Hive



PRODUCT INFORMATION

Part Number	CBS4LEDS-DIF-MS-HL-HV
MIC	AUB02810050002
Description	Odyssey Diffused 1200mm Emergency Batten, LP, Motion Sensor, Zoneworks XT Hive
Construction	Powder coated steel body with acrylic prismatic diffuser and PC/ABS end caps
Mounting	Surface Mount
Dimensions L x W x H	1274mm x 120mm x 110mm
Weight	3.6kg
Operating Mode	Sustained Minimum to maximum light control via the microwave sensor. Low level comfort light when no presence detected ramping to maximum when presence detected
Testing System	Zoneworks XT HIVE (RF)
Battery	Lithium Iron Phosphate 3.2V 3200mAH
Charging Method	Intelligent Current Limited Constant Voltage
Diffuser	Acrylic Prismatic
Driver / Ballast	Hytronik HED1050H/C
Lamp(s)	LED strip module, 4,000K natural white, 50,000h life [L70/B50 Ta 40°C], Ra>80
Operating Voltage	240V AC; 50Hz
Power Factor	0.95
Power Consumption	1.2W/45.7W (STDBY/MAX)
Inrush Current (Max)	TBC
Earth Leakage	0.080mA
Total Lumen Output	4585lm @112lm/W
Operating Temperature	1°C to 40°C
IP Rating	IP20
Impact Rating	N/A
AS2293 Classification	C0=40, C90=40
Applicable Standards	AS/NZS3820, CISPR15, AS/NZS2293.3
Compliance Marking (RCM)	

REPLACEMENT PARTS

PART NUMBER	DESCRIPTION
1550050	Battery
8002695	LED Strip x 2
1100635	EM LED
1330059	240V Driver
AUM02870100001 CLIFE-CKIT-HVEXTA-NP	Emergency Driver
8001394	HIVE Node

The product details described in this document are current as at the version date of the document. We reserve the right to change product design, specifications or materials (Specifications) as part of our continuous improvement program. Please confirm the applicable Specifications at the time of placing your order.