



CBS4LEDS-DIF-MS-HL

Odyssey Diffused 1200mm Emergency Batten, LP, Motion Sensor, Clevertest Plus



PRODUCT INFORMATION

Part Number	CBS4LEDS-DIF-MS-HL
MIC	AUB02310080002
Description	Odyssey Diffused 1200mm Emergency Batten, LP, Motion Sensor, Clevertest Plus
Construction	Powder coated steel body with acrylic prismatic diffuser and PC/ABS end caps
Mounting	Surface mount
Dimensions L x W x H	1274mm x 120mm x 110mm
Weight	3.7kg
Operating Mode	Sustained
Testing System	Clevertest Plus Enabled (Not activated by default)
Battery	Lithium Iron Phosphate, 3.2V 3200mAh
Charging Method	Intelligent Current Limited Constant Voltage
Diffuser	Acrylic Prismatic
Driver / Ballast	Hytronik HED1050H/C
Lamp(s)	LED strip module, 4,000K natural white, 50,000h life [L70/B50 Ta 40°C], Ra>80
Operating Voltage	240V AC; 50Hz
Power Factor	0.95
Power Consumption	1.0W/45.5W (STDBY/MAX)
Inrush Current (Max)	TBC
Earth Leakage	0.084mA
Total Lumen Output	4585lm @112lm/W
Operating Temperature	1°C to 40°C
IP Rating	IP20
Impact Rating	N/A
AS2293 Classification	C0=40, C90=40
Applicable Standards	AS/NZS3820, CISPR15, AS/NZS2293.3
Compliance Marking (RCM)	

REPLACEMENT PARTS

PART NUMBER	DESCRIPTION
1550050	Battery
8002695	LED Strip x 2
1330070	240V Driver
AUM02370170001 CLIFE-CKIT-NP	Emergency Driver

The product details described in this document are current as at the version date of the document. We reserve the right to change product design, specifications or materials (Specifications) as part of our continuous improvement program. Please confirm the applicable Specifications at the time of placing your order.